

**BX3780**  
**2007-11 Toyota Yaris**  
(No S Model or Hatchback)  
Installation Instructions

**Serial Number**

**Please read BOTH these Installation Instructions and the General Towing Instructions before attempting to install or operate this**

1. Blue Ox® towing products and accessories are intended to be installed by Blue Ox® Dealers who are familiar with our products and have the equipment and knowledge to do “fit work.” When necessary, Blue Ox® Dealers can be found at [www.blueox.com](http://www.blueox.com) or by contacting our Customer Care Department at (402) 385-3051.

Attachment Tab Height: 14”  
Attachment Tab Width: 24”

2. Many Blue Ox® Baseplates are designed to use existing holes and hardware to mount the baseplate to the towed vehicle. Even though bolts are there, do not assume they are adequate for baseplate mounting. Always use hardware supplied in the hardware kit or existing hardware specified in the Baseplate Towing Installation Instructions.

**Bolt Torque Specifications**

Torque in Foot-Pounds for Metric Bolts

Bolt Size	Grade 8.8	Grade 10.9
6MM	6	8
8MM	16	22
10MM	31	40
12MM	54	70
14MM	89	117

Confirm the towability and pre-towing procedures for your vehicle with the owner’s manual or contact the vehicle’s manufacturer for specific towing procedures.

**Bolt Torque Specifications**

Torque in Foot-Pounds for Inch Bolts

Bolt Size	Grade 5	Grade 8
1/4”	10	14
5/16”	19	29
3/8”	33	47
7/16”	54	78
1/2”	78	119
5/8”	154	230



**! WARNING**

Failure to read and follow these instructions could result in separation of the towed vehicle from the tow bar, causing property damage, loss of towed vehicle, personal injury or death.

# BX3780

## 2007-11 Toyota Yaris (No S Model or Hatchback)

### Installation Instructions


## Parts List

Ref. No.	Qty.	Part #	Description
1	1	61-6542	WLDM'T, BP, BX3780
2	1	101-7241	PLATE, SUPPORT, DS, BX3780
3	1	101-7242	PLATE, SUPPORT, PS, BX3780
4	2	102-6861	SPACER PLATE, BX3778
5	8	61-5208	WLDT, NUT PLT, 1/4X1X1, 3/8 BLT WIR
6	4	201-0440	3/8-16 X 1 1/2 HEX BOLT, GRD.5, ZP
7	8	201-0368	3/8-16 X 1 1/4 HEX HEAD BOLT,GRD. 5
8	4	201-0443	3/8-16 X 1 HEX BOLT GRD.5, ZP
9	16	203-0010	3/8 LOCK WASHER, ZP
10	8	202-0003	3/8-16 HEX NUT, ZP
11	2	201-0553	1/4-20 X 1/2 HX.WSHD.TYPE F TCS, ZP
12	2	201-0192	10-32 X 1/2 SLOT, RD. HD. SCREW
13	2	203-0054	#10 LOCK WASHER
14	2	202-0047	#10-32 HEX NUT
15	2	101-5822	ADAPTER, 4 WAY CONNECTOR
16	2	62-3468	ATT TAB ASSY, REM, SF/SB, 1 HOLE
	2	226-0046	BASEPLATE SAFETY CABLE, 36" CL III (not shown)
	4	229-0359	QUICKLINK, 3/8", ZP (not shown)
	2	290-0437	RECEIVER, CAP PLUG (BLK) (not shown)

## Tools Required

10MM Socket	9/16" Socket
Large Vise Grip	13/32" Drill Bit
Flat Screw Driver	Utility Knife

Loctite® RED



### Important:

Use only genuine factory replacement parts on your baseplate. Do **NOT** substitute homemade or non-typical parts. If a bolt is lost or in need of replacement, for your safety and the preservation of your baseplate, be sure to use a replacement bolt of the same grade (In most cases it will be Grade 5, please reference the parts list above). Replacement parts may be ordered through your nearest Blue Ox® Dealer or Distributor. Failing to follow and/or altering these installation instructions in either installation or required equipment will void the manufacturer's warranty. Towing behind a non-motorized vehicle will void the warranty.

BX3780

# 2007-11 Toyota Yaris

(No S Model or Hatchback)

## Installation Instructions

### Vehicle Weight:

Due to the design of the removable tabs, the RangeFinder II tow bar can not be used. Adapters, except the BX8833 and BX88151, can not be used with this baseplate.

**Installation Notes:** The fascia, washer reservoir and horn are removed and reinstalled during installation of the baseplate. Drilling is required. Trimming is required.

The dimensional variations between otherwise identical vehicles can be considerable. While the baseplate was designed for easy installation, it may be necessary to tailor the baseplate slightly to compensate for auto manufacturer's tolerances. These minor adjustments may include filing a hole slightly, bending electrical rods or bending end plates.

The BX8869 Bulb and Socket Wiring Kit is recommended for this vehicle.



**Possible Location of the BX8869 Bulb & Socket Wiring Kit**

Handling of some cosmetic parts when installing this product may require the use of protective covers, rags, specialty tools, etc. to prevent damage.

### Installation Instructions:




1. Push in center to remove six plastic push pins from the top edge of the fascia. Set push pins aside to be reinstalled later.





2. Just forward of the front tire next to the wheel well edge on the bottom side of the fascia, remove the metric bolt with a 10MM socket. Do this to both sides of vehicle. Set bolts aside to be reinstalled later.

BX3780  
2007-11 Toyota Yaris  
(No S Model or Hatchback)  
Installation Instructions



3. Remove eight metric bolts from lower edge of fascia all the way around using a 10MM socket. Pull fascia corners out to the side of the vehicle on both sides, then forward. Set bolts and fascia aside carefully for later reinstallation.




4. Unhook and pull out the five hose clamps. On the driver's side, remove the brace (gray arrow) and move the hose. Set clamps aside for later reinstallation.
5. Using a 14MM socket, remove three bolts from the bumper core. Using a 10MM socket, remove two hex nuts (gray arrows). Do this on both sides. Set bolts aside for later reinstallation.




6. On the passenger side, use a 10MM socket to remove three bolts from each side of the headlight. Set headlight and bolts aside for later reinstallation.
7. Using a 10MM socket, remove one bolt from each side of washer reservoir. Unplug electrical connections and hoses. Lift washer reservoir up and out to the side to remove. Set aside for later reinstallation.

BX3780  
2007-11 Toyota Yaris  
(No S Model or Hatchback)  
Installation Instructions




8. Using a 14MM socket, remove four bolts from above and below the frame extension. Do this on both sides. Set frame extension and bolts aside for later reinstallation.

**Using a good quality paint, spray cut edges of frame to prevent rusting.**



9. After the frame extension is removed, measure 1" up from the bottom and cut across using a reciprocating saw, bend in. Trim following the seam up until just under the notch then connect straight across (gray arrow). Do this on both sides.



10. Using a reciprocating saw, cut a notch starting 5/8" up from the bottom and across in the lower frame support webbing and cut it out. Do this on both sides.




11. On the bottom side of the bumper, using a reciprocating saw trim back 2" of lower webbing. Do this on both sides.




12. Behind the frame, cut the plastic belly pan 3" down and 1 3/4" in. Do this on both sides.


BX3780  
2007-11 Toyota Yaris  
(No S Model or Hatchback)  
Installation Instructions



13. Using a reciprocating saw, cut above the bolt in the frame horizontally and then diagonally up and remove the notch. Do this on both sides.



14. Line up the two big existing holes in the frame extension with the side baseplate holes. Start the 3/8-16 x 1 1/4" bolts with 3/8" lock washers and on the inside of the frame use 3/8-16 nut plate. Do this on both sides.



15. Using the baseplate as a template, drill the two bottom holes into the frame extension. Install 3/8-16 x 1 1/4" bolts and lock washers into drilled holes. Then tighten into 3/8 nut plates inside extension. Do this to both sides.


When using power drills, be aware of the dangers of torque and drill bit length.

**BE SURE TO USE LOCTITE® RED ON ALL BOLTS BEFORE TIGHTENING. TIGHTEN ALL BOLTS ACCORDING TO THE TORQUE CHART ON THE FRONT PAGE OF THESE INSTRUCTIONS OR ON PAGE 3 OF THE BASEPLATE TOWING GENERAL INSTRUCTIONS.**




16. Reinstall the frame extension with two bolts on the top and two on the bottom. Do this on both sides.


BX3780  
2007-11 Toyota Yaris  
(No S Model or Hatchback)  
Installation Instructions




17. On the driver's side, use a 10MM socket to remove two bolts and the air bag sensor. Carefully set sensor up out of the way for later reinstallation.



18. Put the side plate on with one 3/8-16 x 1" bolt (white arrows) with 3/8" lock washer and 3/8" hex nut, while drilling the back two holes into lower frame webbing with the 13/32" drill bit. When drilling be aware of the brake lines behind lower webbing. Loosen the first bolt, insert 3/8-16 x 1 1/2" bolt with Loctite, the spacer plate and 3/8" lock washer with 3/8" hex nut in the back and tighten. Then tighten the front two bolts with Loctite. Do this on both sides. On the driver's side, the bolts protrude to the outside.



19. Reattach the air bag sensor. Put the bumper back on the original position. Plug the cables back in on top of the bumper.




20. Reinstall the horn.


BX3780  
2007-11 Toyota Yaris  
(No S Model or Hatchback)  
Installation Instructions



21. Trim the air dam down to the first ridge, all the way across and back to the second to the last ridge. Do this on both sides.



22. On the front of the air dam is a temperature sensor, squeeze the tabs together on the back side and remove. Use a 1/4" drill bit to put a slot 3/4" back from the original hole (gray arrow). Snap sensor into new position.



23. On the passenger side, reinstall the washer reservoir.
25. Reinstall the headlight and fascia. Reconnect all electrical connections and clamps.

Be sure that **ALL** electrical connections are plugged in properly and functioning **BEFORE** installing the fascia.

Install the tow bar and safety cables according to the instructions provided in their packages. When demonstrating to customer, be sure to include all original content and packages. Do **NOT** substitute other devices if the tow bar pins and clips are misplaced.



24. Attach the permanent baseplate safety cables to the provided convenience link on the baseplate (grey arrow). The photo above shows the recommended installation of the cables to frame of vehicle (white arrow). Additional options may interfere with suggested mounting; in this case secure the cables to a solid piece of the frame as described in the instructions included with the permanent baseplate safety cables. Be sure the safety cables do not rub against any hoses or moving parts. Do this to both sides of the vehicle.



BX3780

# 2007-11 Toyota Yaris

(No S Model or Hatchback)

## Installation Instructions

**DEALER or INSTALLER:**  
Be certain the user receives the instruction sheets for their products.



**Shown without removable tabs installed.**



**Shown with removable tabs installed.**

If the baseplate is in an accident, it must be replaced. DO NOT use it again! An accident can cause unseen damage and using it again could result in more damage or serious injury. DO NOT use the baseplate if it is damaged or missing parts.

## CUSTOMER SERVICE COMMITMENT

Blue Ox is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.



© 2011 Blue Ox  
One Mill Road, Industrial Park  
Pender, Nebraska 68047  
Phone: (402) 385-3051 • Fax: (402) 385-3360  
[www.blueox.com](http://www.blueox.com)