



Windbreaker

1987-1995 YJ Wrangler

1997-2006 TJ Wrangler

1980-1983 CJ-5

1976-1986 CJ-7, 8

Part #: WB10015, WB10035, & WB10037

Kit Components:

- Windbreaker
- Footman Loops (2)
- Sheet Metal Screws (4)

-Read all instructions carefully prior to starting installation.

-We recommend installing this in temperatures 70F (21C) and above. This will make installation easier and reduce the risk of damaging the windbreaker. Laying the windbreaker in the sun is also suggested to ease installation.

-Do not over-stress the straps. Failure to comply may damage the fabric or straps.

-Drilling may be required.



1. Position the Windbreaker inside the center roll bar hoop with the gray side facing the front seats.
2. Wrap the straps around the back of the roll bar, over, and down to the buckles. Loosely fasten the straps to the buckle. Once all of the straps are fastened to the buckles they can be tightened.
3. Make any adjustments necessary to ensure the top is centered and fits properly. Creases in the top fabric of windows will fade away once the top is installed.
4. Small adjustments to the top may be necessary once the top warms up and any creases are smoothed out.

To Attach the Windbreaker to the Floor (Optional)

1. Align the supplied Footman Loops with the straps located at the bottom of the Windbreaker, taking care to keep the straps as straight as possible. Using the Footman loop as a template, mark the hole location on the floor of the vehicle.
2. Using a 1/8" drill bit, drill holes into the floor at the previously marked locations.
3. Use the Sheet Metal Screws to secure the footman loops to the floor. Place the straps through the footman loops and buckles and tighten for a snug fit.

To Attach the Windbreaker to the Tonneau Cover

NOTE: The RT Off-Road Windbreakers are only intended to work with RT Off-Road Tonneau Covers.

1. With both the Windbreaker and Tonneau Cover installed, snap the fabric adapter strip (included with the Tonneau Cover) to the Windbreaker and Tonneau Cover.

While every attempt is made to ensure that the information contained in these instructions is correct, no liability can be accepted by the authors for loss, damage, or injury caused by any errors in, or omissions from the information given. All service should be performed by qualified mechanics. Crown Automotive Sales Co., Inc. cannot be held responsible for any mechanical work performed. Standard and accepted safety precautions should be used in every procedure.