

**OPEN FIRST!**

## Installation Instructions

For Set # 2.9105

Rear Tailgate Tire Bumper  
2007+ Jeep JK (all models)

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673

© 2015 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

It is recommended that if you are unfamiliar with this type of work that you refer to a qualified service center specializing in this type of work. Energy Suspension recommends that you thoroughly read over all the installation instructions and check all P/N's and quantities in the Parts List before you start. Call customer service at 949-361-3935 if the parts in your kit do not match this Parts List.


### Tailgate Tire Bumper Removal/Installation:

1. Loosen lug nuts and remove spare tire/wheel from rear of vehicle
2. Remove OE tailgate tire bumper by firmly grasping and pulling out at an angle
3. Trim your new polyurethane tire bumper to the desired length using a hack saw or razor blade. Polyurethane is difficult to cut so **BE CAREFUL!** When trimming, be sure that the tire bumper is long enough to contact the spare tire with approx. 1/4" of engagement for optimal vibration isolation
4. Install the new polyurethane tire bumper by firmly pressing the small nub into the oval hole on your tailgate. The bumper will snap in place when fully installed
5. Reinstall your spare tire/wheel and torque lug nuts to factory specs



### Parts list:

- 2 - 06P06369  
(Tailgate Tire Bumper)
- 1 - 17P17666  
(This Instruction Sheet)



**17P17666**

16/DEC/15 MAX ECN 15131

**OPEN FIRST!**

## Installation Instructions

For Set # 2.9105

Rear Tailgate Tire Bumper  
2007+ Jeep JK (all models)

**ENERGY**  
**SUSPENSION**®

1131 VIA CALLEJON, SAN CLEMENTE, CA 92673

© 2015 Energy Suspension. All rights reserved.  
May not be reproduced, in any form, or by any means,  
without the written consent of Energy Suspension.

It is recommended that if you are unfamiliar with this type of work that you refer to a qualified service center specializing in this type of work. Energy Suspension recommends that you thoroughly read over all the installation instructions and check all P/N's and quantities in the Parts List before you start. Call customer service at 949-361-3935 if the parts in your kit do not match this Parts List.


### Tailgate Tire Bumper Removal/Installation:

1. Loosen lug nuts and remove spare tire/wheel from rear of vehicle
2. Remove OE tailgate tire bumper by firmly grasping and pulling out at an angle
3. Trim your new polyurethane tire bumper to the desired length using a hack saw or razor blade. Polyurethane is difficult to cut so **BE CAREFUL!** When trimming, be sure that the tire bumper is long enough to contact the spare tire with approx. 1/4" of engagement for optimal vibration isolation
4. Install the new polyurethane tire bumper by firmly pressing the small nub into the oval hole on your tailgate. The bumper will snap in place when fully installed
5. Reinstall your spare tire/wheel and torque lug nuts to factory specs



### Parts list:

- 2 - 06P06369  
(Tailgate Tire Bumper)
- 1 - 17P17666  
(This Instruction Sheet)



**17P17666**

16/DEC/15 MAX ECN 15131