


SEAT COVERS
BY**SUPER-GRIP® THE SLIP RESISTANT FASTENING SYSTEM****INSTALLATION INSTRUCTIONS
FOR
DT72-66****CUSHION COVERS**


1. Center cover on seat
2. Lift cushion to halfway up position and pass back flap through crevice
3. With cushion in up position locate straps and buckle to back flap
4. smooth out cover and adjust straps to equalize tension for a better fit

BACKREST COVER

1. Ensure cover is installed under seat belt strap
2. Place cover over backrest. Cover has allowance to fit over headrest. (see notes)
3. Undo Velcro and place around headrest post to reduce cover movement during installation. Tuck material behind the seat for better fit.
4. Pass side Velcro behind the seat and attach to the bottom of cover
5. **DRIVERS SIDE.** Pass center strap through opening on metal seat belt base on floor and buckle
6. **PASSENGER SIDE.** Anchor each center strap on metal seat belt base on the floor and buckle
7. Install adhesive back Velcro (included) on inside edge of armrest well to align with Velcro on seat cover. (see note below)
8. Smooth out cover and adjust straps/velcro to equalize tension for a better fit.

D) ARMREST COVER

- 1) Fold down armrest
- 2) Slip cover over armrest and attach velcro
- 3) Position adhesive Velcro supplied to align with Velcro on cover around the edge of cup holder and on top. (see note below)

NOTES:**1) SELF-LOCKING SUPER-GRIP® BUCKLE:****2) FOR DT72-66 INSTALLATION**

Undo Velcro on cover, place around headrest post and attach

3) ADHESIVE BACK VELCRO

Before positioning Velcro, clean area with alcohol swab provided.

WARNING: SEATS WITH INTEGRATED SEAT AIRBAGS MUST BE COVERED ONLY WITH SEATCOVERS DESIGNED WITH OPENINGS THAT WILL NOT INTERFERE WITH THE DEPLOYMENT OF THE AIRBAG. NEVER INSTALL SEAT COVERS WITHOUT THESE OPENINGS AS THIS MAY INTERFERE WITH THE PROPER DEPLOYMENT OF THE AIR BAGS AND COULD RESULT IN SERIOUS INJURY.



Fia Inc. Winnipeg, Canada R3L 0N3 Telephone (204) 475-0515 Toll-Free: 1-800-835-0438
Fax: (204) 284-8246 E-Mail: info@gofia.com Website: www.gofia.com

DURA-TECH PRO 5 YEAR WARRANTY

Fia Inc. guarantees the original purchaser a limited 5 year warranty against manufacturer's defects in materials, workmanship and finish under normal use. The warranty is void if the product has been damaged resulting from product misuse, improper installation, product modifications or product neglect. The warranty applies to all Fia Dura-Tech Pro products and is limited to repair or replacement of the product. Warranty does not include cost of removal, installation, labor, freight and incidental or consequential damages.

Original purchaser must return defective merchandise along with the original purchase receipt to the original place of purchase for repair or replacement. Shipping charges will apply for any repair or replacement.

Buyer assumes all risk and liability whatsoever from the installation of Fia products. Vehicles equipped with supplemental restraint systems (air bags) deployed by impact should not be modified or covered by any aftermarket seat cover without consulting the vehicle manufacturer and Fia Inc. Fia Inc. assumes no liability for injury, loss, incidental or consequential damages in the event of an accident.