



FORD PERFORMANCE

M-6049-SCJ SUPER COBRA JET CYLINDER HEAD – BARE Fits 429 and 460 ci engines (except BOSS 429)

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD PERFORMANCE PARTS © Ford Motor Company 2020

PRIOR TO INSTALLATION READ THESE INSTRUCTION COMPETELY
For questions, Call the FORD PERFORMANCE Techline 1-800-367-3788

Please visit <https://www.performanceparts.ford.com> for warranty information

OVERVIEW:

This instruction sheet contains important information regarding dimensions and specifications of the M-6049-SCJ cylinder heads. This is a bare cylinder head that comes un-assembled. These cylinder heads are set up for valves that are on different locations, angles and larger than stock, and therefore piston to valve clearance must be checked. This check includes both radial and depth clearance checks. Radial clearance .060" minimum, depth on intake .080" and .120" on exhaust. These heads use stud mounted rocker arms, rocker arm to valve cover clearance must also be checked. These instructions should be reviewed by all engine builders, due to minor changes that could impact the engine assembly process.

CONTENTS/BILL OF MATERIALS:

PART #	DESCRIPTION	QUANTITY
M-6049-SCJ	Bare un-assembled cylinder head	1

FEATURES AND SPECIFICATIONS:

Head material	A356 aluminum
Intake port location	Stock Super Cobra Jet
Intake port volume	290 cc
Intake guide material	Manganese-bronze
Intake valve stem diameter	11/32"
Intake valve seat material	Ductile iron
Exhaust port location	Stock Super Cobra Jet
Exhaust port volume	148 cc
Exhaust guide material	Manganese-bronze
Exhaust valve stem diameter	11/32"
Exhaust valve seat material	Ductile iron
Combustion chamber volume	72 cc
Valve guide clearance intake	.0012-.0022"
Valve guide clearance exhaust	.0016-.0026"
Weight	Approximately 32#

TYPICAL AIR FLOW

LIFT	INTAKE CFM	EXHAUST CFM
0.100	68.5	53.3615
0.200	134.1	95.59
0.300	197.5	131.93
0.400	264.3	167.455
0.500	317.4	187.8
0.600	324.1	195.625
0.700	324.1	203.45

Ford Factory Shop Manual purchase options www.motorcraftservice.com



FORD PERFORMANCE

M-6049-SCJ
SUPER COBRA JET CYLINDER HEAD – BARE
Fits 429 and 460 ci engines (except BOSS 429)

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF
FORD PERFORMANCE PARTS © Ford Motor Company 2020

RECOMMENDED PARTS

Intake valve part number	M-6507-B429
Exhaust valve part number	M-6505-A429
Intake gasket	Fel-Pro 1231
Exhaust gasket	Fel-Pro 1420
Valve covers	M-6582-C460
Engine block	M-6010-A460X or M-460-A460XBB (Big bore version)
Harmonic damper	M-6316-A521
Timing chain set	M-6268-B429
Water pump	M-8501-C460
Spark plugs	AGSP32C

RECOMMENDED TORQUE VALUES

Head bolt	9/16-12 Head bolt torque is 135 lb*ft, torque in steps 70/105/135 lb*ft
Intake manifold	35lb*ft, torque in steps 20/35 lb*ft
Exhaust manifold	35 lb*ft, torque in steps 20/35 lb*ft
Valve cover	8-10 lb*ft
Rocker studs	65 lb*ft
Spark plugs	10-12 lb*ft

Ford Factory Shop Manual purchase options www.motorcraftservice.com