

HOW TO DETERMINE WHICH EXECUTIVE YOU NEED

1. Determine which connection you're looking for:

- a.) Standard Fifth Wheel Connection
- b.) Gooseneck Connection: eliminates the need for a bulky fifth wheel hitch in the bed of your truck! ***Comes with our Automatic SnapLatch Coupler*

2. Confirm your trailer's frame model:

- a.) Sometimes the frame model number can be found on your original pin box.
- b.) If you're unable to locate this model number, refer to the spec sheets on our website to determine which bolt pattern matches the bolt pattern on your unit.
- c.) Contact the frame or trailer manufacturer if unknown.

3. Determine which size EXECUTIVE you need:

***NOTE: DO NOT GO BY THE HITCH/PIN WEIGHT LISTED ON YOUR TRAILER**

- To calculate your loaded pin weight, take 22% of your trailer's GVWR.
EXAMPLE: 16,800 LB. GVWR x 0.22 = 3,696 LBS. / You will want to go with the **5.5K** model
- Below is a guide showing which size model you need based on the calculated pin weight you come up with:

If you calculated **1,600 - 2,599 LBS**, go with the **3.5K** model

If you calculated **2,600 - 3,599 LBS**, go with the **4.5K** model

If you calculated **3,600 - 4,599 LBS**, go with the **5.5K** model

If you calculated **4,600 - 5,599 LBS**, go with the **6.5K** model

If you calculated **5,600 - 6,599 LBS**, go with the **7.5K** model

If you calculated **6,600 - 7,599 LBS**, go with the **8.5K** model

- Do you have the Lippert 1116 or 1716 frame model? **Purchase the Shim Kit: GH-8000**
- Ordering a Fifth Wheel to Gooseneck model? **Purchase the Safety Chains: GH-70684**
- Need new hardware for installation? **Purchase the Bolt Installation Kit: GH-80943**
- Are you using a sliding fifth wheel hitch? **Purchase the Capture Plate: GH-70924**

If you have any questions, feel free to email sales@genyhitch.com or call (574) 218-6363!