



## #3267 TORQUE-CURVE MPFI SPACER

2007-Up Chevy/GMC 1500, 2500, 3500  
Trucks & SUVs with 4.8L, 5.3L, 6.0L, 6.2L  
2005-06 Pontiac GTO 6.0L  
2005-07 Chevrolet Trailblazer 5.3L  
2005-07 GMC Envoy 5.3L

### INSTALLATION INSTRUCTIONS

Important! Read all instructions before you begin installation.

#### THIS KIT CONTAINS

- |                                    |                        |
|------------------------------------|------------------------|
| 1 - Hamburger's Performance Spacer | 4 - 6mm X 60mm Bolts   |
| 1 - O-ring                         | 4 - 6mm Flat Washers   |
| 1 - 3/4" Extension Plate           | 1 - 6mm Flat Head Bolt |

#### TOOL LIST

- 10mm Deep Socket  
4mm Sockets  
5/32" Allen Wrench

1. **DISCONNECT NEGATIVE (-) BATTERY CABLE.**
2. Lift up on the front of the beauty cover and remove it from the engine area (Ref. 1). Then push down on the radiator hose and separate the tube from the plastic clamp.
3. Gently pull the breather tube towards you to disconnect it. Then loosen the hose clamp on the intake tube at the throttle body (Ref. 2), and at the other end, and remove the tube from the engine area.
4. With a 10mm socket remove the (2) nuts and the (2) bolts that hold the throttle body to the intake manifold (Ref. 3). Set the throttle body aside. Don't disconnect the wiring harness.
5. Using a 4mm socket, remove the (2) studs from the manifold.
6. Install the (1) O-Rings on Hamburger's Spacer (You may need to stretch slightly for fitting).
7. Install the Hamburger's Spacer with throttle body using (4) 6mm x 60mm bolts & (4) 6mm flat washers (Ref. 4).  
**Note: The O-ring side of the spacer faces the throttle body.**
8. Remove the "Ball Stud" from the top of the intake manifold (Ref. 5). With the 6mm flat head bolt, install the 3/4" Extension Plate by threading the bolt into the hole where you removed the "Ball Stud" from. Face the spacer toward the front of the vehicle and tighten bolt with the 5/32" allen wrench. Next thread the "Ball Stud" into the forward hole in the 3/4" extension plate and tighten (Ref. 6).
9. Remove the factory grommet from the intake tube and install it on the "Ball Stud" with the small diameter facing upward (Ref. 7).
10. Reinstall the intake tube (using caution to center the intake tube hole over the grommet just installed). Some adjustments may be required to seat the grommet correctly back into the intake tube. Tighten the hose clamps on the tube.
11. Reconnect the breather tube and the plastic clamp from step 2. Then reinstall the beauty cover (Ref. 8).
12. Reconnect negative battery cable.



Ref. 1



Ref. 2



Ref. 3



Ref. 4



Ref. 5



Ref. 6



Ref. 7



Ref. 8