





757-842-6497
WWW.JLOSC.COM

J&L 3.0 Oil Separator CONVERSION Kit (converting 3011P to 3020P)
2011-17 Mustang GT w/ Roush/Whipple/FRPP Supercharger, Passenger side
3011PCK-3020P

Installation Instructions

Please review complete instructions prior to installing.

1	Verify you have all of the following parts included in the kit: (1) Hose tree with check valve and PCV connection, (1) short hose with straight PCV connection, (2) hose end caps
2	Gather all of the following tools needed for the installation: Dykes/cutters, 18mm wrench or long #3 screwdriver and light oil.
3	<p>Cut off crimps from the hose connections on the 3011P separator and remove hoses from fittings.</p> 
4	<p>Once hoses are removed, you will need to move the 90° fitting to point downward. Use 18mm box end wrench to do this, or long screwdriver shoved into the end of the fitting to move it.</p> 

Install short hose with straight PCV connection onto the straight fitting on the can.

TIP: Use a drop of oil to help with lubrication in sliding the hose onto the fitting. If using the supplied dress up pieces be sure to put those onto the hose first. Install the larger hose assembly onto the 90 degree side the same way. The longer section of the hose should be in front of the OSC logo on the can. See picture below



5

6 You are done! Follow 3020P directions from here for install onto the vehicle.

To properly clean the filter in the Oil Separator, spray any degreaser or solvent through it and let it air dry. Clean it every 10,000 miles.

Thank you for your business. If you have any questions, please e-mail info@JLosc.com or call 757-842-6497. Our hours are Monday-Friday. 8:00am – 4:30pm Eastern Time.

J&L Oil Separator co. Lifetime Satisfaction Guarantee. We want you to be a J&L customer for life! Your new J&L product is warranted to be free from defects in materials and workmanship for the life of the *original retail purchaser*, subject to the limitations contained in our warranty found here. www.JLosc.com/warranty

We guarantee workmanship and even a pathway to discounted upgrades for substantially improved items.

Return Policy: All returns will be subject to a 10%-25% restocking fee. Please visit www.JLosc.com for complete return policy.

Disclaimer: J&L Oil Separator co. makes no warranties whatsoever, expressed, or implied, oral or written to any purchasers, except the warranty above. J&L Oil Separator co. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by J&L Oil Separator co. agree to hold harmless and indemnify J&L Oil Separator co. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to J&L Oil Separator co. for any claims arising out of use of its products.