

Viscoplus for Oil

Description

Mono functional additive that stabilizes motor oil viscosity. Provides outstanding protection against mechanical and permanent shear losses in extreme conditions and prevents viscosity loss caused by frequent cold starts.

Properties

- stabilizes loss of viscosity
- optimum lubrication under all operating conditions
- fully compatible with mineral and synthetic oils
- reduces engine noise
- optimum oil pressure under all operating conditions
- reduces oil consumption
- improves the movable seal between piston and cylinder
- reduces wear

Technical data

Color / appearance	hellbraun / light brown
Density at 68 °F	0,89 g/cm ³ DIN 51757
Viscosity at 68 °F	2400 mPas DIN 51377
Flash point	214 °F DIN ISO 2592
Pour point	23 °F DIN ISO 3016
Odor	charakteristisch / characteristic
Form	flüssig / liquid

Areas of application

For all 4-stroke gasoline and diesel engines, with or without turbochargers. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

Application

Contents (300 mL) is sufficient for 3–5 Liters (0.8 gal. to 1.3 gal.) motor oil. After adding to the motor oil, allow the engine to run warm. The product can be added at any time.

Comment

Not suitable for use on motorbikes with wet clutches.



Available pack sizes

300 ml Can sheet metal	20206 USA (-EN-)
300 ml Can sheet metal	20338 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.