Product information

PI 39/12/10/2020

Synthoil Race Tech GT1 SAE 10W-60



Description

Fully synthetic motor oil designed for extreme conditions. Developed specifically for high output, high performance engines. The wide viscosity range and unique formulation provides outstanding thermal stability for proper lubrication and low engine wear in tough conditions.

Properties

- outstanding engine cleanliness - mixable with most engine oils - high lubrication reliability

- tested for the use with catalytic converters

- optimum stability to aging

- optimum lubrication in extreme operating conditions

- instant lubrication after cold start - extremely low oil consumption

- extremely low evaporation loss

Technical data

Flash point 464 °F

DIN ISO 2592

Total base number 10,5 mg KOH/g

DIN ISO 3771

Sulfate ash 1,0 - 1,6 g/100g

DIN 51575

Color number (ASTM) 3.5

DIN ISO 2049

Specifications and approvals:

ACEA A3 • ACEA B4 • API SN

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-H3

Areas of application

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

Technical data

SAE class (engine oils)	10W-60 SAE J300
Density at 59 °F	0,855 g/cm³ DIN 51757
Viscosity at 104 °F	168,0 mm²/s ASTM D 7042-04

Viscosity at 212°F 24.0 mm²/s

ASTM D 7042-04

Viscosity at -22 °F (MRV) < 60000 mPas ASTM D4684

Viscosity at -13 °F (CCS) < 7000 mPas

ASTM D5293

175

Viscosity index

DIN ISO 2909

HTHS at 302 °F ≥ 3.5 mPas

ASTM D5481

-33 °F Pour point

DIN ISO 3016

Evaporation loss (Noack) 5.3 %

CEC-L-40-A-93

Application

Observe the manufacturers instructions!

Available pack sizes

- 1	Canister	nlactic	2068
ιι	Canister	blastic	ZU00

USA AND CANADA (-EN-

F-l

2024 5 l Canister plastic

USA AND CANADA (-EN-

F-l

20 l Canister plastic

USA AND CANADA (-EN-

F-)

60 l Drum sheet metal 20374

USA AND CANADA (-EN-

F-)

205 l Drum sheet metal 20375

USA AND CANADA (-EN-

F-l

1000 l Container 1772

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de