

Motorbike Fork Oil SAE 5W light

Description

Full synthetic, low-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

Properties

- lasting corrosion protection
- prevents foam formation
- increases driving safety
- very wear resistant
- prevents seals from swelling

Technical data

Density at 59 °F	0,825 g/cm ³ DIN 51757
Viscosity at 104 °F	18,0 mm ² /s ASTM D 7042-04
Viscosity at 212°F	4,1 mm ² /s ASTM D 7042-04
Viscosity index	131 DIN ISO 2909
Pour point	-98 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.



Available pack sizes

1 l Can plastic	22108 CANADA (-EN-F-)
1 l Can plastic	20094 USA (-EN-)
20 l Canister plastic	20402 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.