

# Product information

## Motorbike 4T Bike-Additive

PI 33/26/08/2020



### Description

Removes deposits from the fuel system, valves, spark plugs and the combustion chamber while preventing new deposit formation. Improves engine performance and lowers emissions. Provides corrosion protection throughout and prevents carburetor icing.

### Properties

- optimizes engine performance
- prevents corrosion
- reduces residues
- environmentally friendly
- tested for the use with catalytic converters
- increases operational reliability
- for carburetor and fuel-injection engines
- very economical
- reduces the risk of knocking combustion
- normalizes fuel consumption and exhaust emissions values

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>142 °F
Pour point	-49 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 104 °F	<7 mm <sup>2</sup> /s
Density at 59 °F	0,765 g/cm <sup>3</sup>

### Areas of application

Suitable for all 4-stroke gasoline engines. Safe with catalytic converters.

### Application

Contents (125 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

### Comment

 **WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



### Available pack sizes

125 ml Can sheet metal	20048 USA (-EN-)
125 ml Can sheet metal	22096 CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**