

Pro Kart

Description

Fully synthetic, race tested and FIA approved, high-performance motor oil. Ensures maximum performance and protection of the engine in all operating conditions. Exceptional lubrication, outstanding engine cleanliness, low friction and minimum wear as well as low exhaust smoke.

Properties

- good corrosion protection
- reduces solid particles created during combustion
- very wear resistant
- self mixing
- high thermal stability
- prevents the build-up of deposits

Technical data

Density at 59 °F	0,963 g/cm ³ DIN 51757
Viscosity at 104 °F	150 mm ² /s DIN 51562
Viscosity at 212°F	14,6 mm ² /s DIN 51562
Viscosity index	95 DIN ISO 2909
Flash point	>464 °F DIN ISO 2592
Pour point	-22 °F DIN ISO 3016
Sulfate ash	0,086 % ISO 3987

Areas of application

For air or water cooled 2-stroke race engines where a motor oil according to current product specifications is required or recommended. Self-mixing. Pre-mix ratio according to manufacturers instructions.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form. **Not suitable for use with special fuels such as Methanol.**



Available pack sizes

1 l Canister plastic

20170

USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.