

# Product information

## Motorbike Engine Flush

PI 35/26/10/2020



### Description

A highly effective formulation for quick and safe removal of deposits from engines before an oil change. A clean engine will provide less wear, lower emissions and improved performance while preventing premature oil degradation.

### Properties

- cleaning and care
- simple to use
- does not attack common sealing materials
- restores the engine to its original performance
- tested for the use with catalytic converters
- for extended service intervals
- very economical

### Technical data

Color / appearance	gelb, trüb / yellow, cloudy
Form	flüssig / liquid
Base	Additiv, Trägerflüssigkeit / additive, carrier liquid
Viscosity at 104 °F	24,12 mm <sup>2</sup> /s
Flash point	142 °F
Pour point	-49 °F
Odor	charakteristisch / characteristic
Density at 68 °F	0,805 g/cm <sup>3</sup>

### Areas of application

Suitable for all 4-stroke engines, with or without wet clutches. Safe with catalytic converters.

### Application

Contents (250 mL) is sufficient for 3–4.5 Liters (0.6 gal. to 1.2 gal.) oil. Add contents to warm motor oil before the oil change. After adding allow the engine to idle for 10 minutes, then drain the oil and change the filter.

### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Available pack sizes

250 ml Can sheet metal	20050
	USA (-EN-)
250 ml Can sheet metal	22098
	CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**