

# Product information

## Diesel Particulate Filter Protector

PI 10/16/09/2020



### Description

Reduces formation of soot during combustion in the engine. Improves engine performance and emissions control. Reduces clogging of the DPF caused by soot as a combustion product.

### Properties

- reduces soot emissions
- regeneration aid for diesel particulate filters
- especially suitable for short trips and city vehicles

### Technical data

|   |   |
|---|---|
| Base  | Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier |
| Color / appearance                              | hellbraun, klar / light brown, clear  |
| Regulation on Flammable Liquids Class (Germany) | A III   |
| Flash point                                     | 145 °F  |
| Pour point                                      | - 97 °F   |
| Form  | flüssig / liquid  |
| Odor  | charakteristisch / characteristic   |

### Areas of application

Added to diesel fuel for all diesel engines with DPF, particularly in modern high pressure engines in passenger and commercial motor vehicles, tractors, construction machinery and stationary engines. Ideally suitable for short distance or short time operated running engine.

### Application

Contents (250 mL) is sufficient for 50–75 Liters (13 gal. to 20 gal.) fuel. For best results and long-term effect add DPF protector every 2.000 km (1.200 miles).

### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Available pack sizes

250 ml Can sheet metal 2000  
USA (-EN-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**