

Snowmobile Motor Oil 2T Pro Race

Description

Fully synthetic high-performance 2-stroke motor oil developed and tested on racing machines. Ensures maximum performance and protection of the engine in all operating conditions. Outstanding lubrication and engine cleanliness, excellent friction and minimum wear as well as less smoke. This oil improves the riding experience!

Properties

- reduces exhaust smoke and optimizes emissions
- prevents the build-up of deposits
- very wear resistant
- good corrosion protection
- residue-free combustion
- self mixing
- high thermal stability

Specifications and approvals:

API TC • ISO L-EGD • JASO FD

Technical data

Density at 59 °F	0,875 g/cm ³ DIN 51757
Viscosity at 104 °F	50 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-48 °C / -54°F DIN ISO 3016
Flash point	100°C / 212°F DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	rot / red

Areas of application

Particularly for air or water cooled 2-stroke engines in Snowmobiles when a motor oil according to current product specifications is required or recommended. Self-mixing. A Pre-mix ratio up to 1:100 makes it perfectly suitable for E-Tec engines.



Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

1 l Canister plastic	20144 USA AND CANADA (-EN-F-)
4 l Canister plastic	20146 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.