

# 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

# Liqui Moly GmbH

Chemwatch: **51-87120** Version No: **2.1.1.1** 

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

## Chemwatch Hazard Alert Code: 1

Issue Date: **15/08/2019** Print Date: **20/08/2019** S.GHS.USA.EN

# **SECTION 1 IDENTIFICATION**

## **Product Identifier**

Product name	20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L			
Synonyms	ot Available			
Other means of identification	Not Available			

## Recommended use of the chemical and restrictions on use

Relevant identified uses	Use according to manufacturer's directions.

## Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH			
Address	rg-Wieland-Strasse 4 Ulm D-89081 Germany			
Telephone	1 1420 0			
Fax	9731 1420 82			
Website	nttp://www.liqui-moly.com/			
Email	Not Available			


# Emergency phone number

- 071				
Association / Organisation	NFOTRAC			
Emergency telephone numbers	+1800 535 5053 (US, Canada & Mexico)			
Other emergency telephone numbers	+1 352 323 3500 (International)			

# **SECTION 2 HAZARD(S) IDENTIFICATION**

# Classification of the substance or mixture

## CHEMWATCH HAZARD RATINGS



0 = Minimum 1 = Low 2 = Moderate 3 = High 4 = Extreme



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Specific target organ toxicity - single exposure Category 3 (narcotic effects)

# Label elements

Hazard pictogram(s)



SIGNAL WORD

WARNING

## Hazard statement(s)

H336 May cause drowsiness or dizziness.

## Hazard(s) not otherwise classified

Not Applicable

Chemwatch: 51-87120 Page 2 of 9 Issue Date: 15/08/2019 Version No: 2.1.1.1 Print Date: 20/08/2019

## 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

#### Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.		
P261 Avoid breathing mist/vapours/spray.			

## Precautionary statement(s) Response

P312	Call a POISON CENTER or doctor/physician if you feel unwell.	
P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.		

#### Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

## Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

#### **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
64742-54-7.	>60	paraffinic distillate, heavy, hydrotreated (severe)
64741-88-4.	1-10	paraffinic distillate, heavy, solvent-refined (severe)
36878-20-3	<2	nonylated diphenylamines

## **SECTION 4 FIRST-AID MEASURES**

## Description of first aid measures

Eye Contact	If this product comes in contact with eyes:  • Wash out immediately with water.  • If irritation continues, seek medical attention.  • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin or hair contact occurs:  ▶ Flush skin and hair with running water (and soap if available).  ▶ Seek medical attention in event of irritation.
Inhalation	<ul> <li>If furnes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> </ul>

# Most important symptoms and effects, both acute and delayed

See Section 11

# Indication of any immediate medical attention and special treatment needed

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- Positive pressure ventilation may be necessary.
- Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- After the initial episode individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment. Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications.
- Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

BP America Product Safety & Toxicology Department

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

Chemwatch: 51-87120 Page 3 of 9 Issue Date: 15/08/2019 Version No: 2.1.1.1 Print Date: 20/08/2019

# 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

## **Extinguishing media**

- ► Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters ► Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Fire Fighting ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area Combustible. ▶ Slight fire hazard when exposed to heat or flame. ► Heating may cause expansion or decomposition leading to violent rupture of containers. ► On combustion, may emit toxic fumes of carbon monoxide (CO). Combustion products include: carbon dioxide (CO2) Fire/Explosion Hazard phosphorus oxides (POx) sulfur oxides (SOx) other pyrolysis products typical of burning organic material. May emit poisonous fumes CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

# **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

See section 8

## **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	Slippery when spilt.  Remove all ignition sources.  Clean up all spills immediately.  Avoid breathing vapours and contact with skin and eyes.  Control personal contact with the substance, by using protective equipment.
Major Spills	Slippery when spilt.  Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

Safe handling	The conductivity of this material may make it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 10 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m., Whether a liquid is nonconductive or semi-conductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.  Containers, even those that have been emptied, may contain explosive vapours.  Do NOT cut, drill, grind, weld or perform similar operations on or near containers.  Electrostatic discharge may be generated during pumping - this may result in fire.  Ensure electrical continuity by bonding and grounding (earthing) all equipment.  Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec).  Avoid splash filling.  Avoid all personal contact, including inhalation.  Wear protective clothing when risk of exposure occurs.  Use in a well-ventilated area.  Prevent concentration in hollows and sumps.

## Store in original containers.

Keep containers securely sealed.

 No smoking, naked lights or ignition sources. ► Store in a cool, dry, well-ventilated area.

# Conditions for safe storage, including any incompatibilities

# Metal can or drum

Suitable container

Other information

- Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks

Chemwatch: 51-87120 Page 4 of 9

Version No: 2.1.1.1

## 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

Issue Date: 15/08/2019 Print Date: 20/08/2019

Storage incompatibility

CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire

► Avoid reaction with oxidising agents

## **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

# **Control parameters**

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	paraffinic distillate, heavy, hydrotreated (severe)	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m3	10 mg/m3	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	paraffinic distillate, heavy, hydrotreated (severe)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
US OSHA Permissible Exposure Levels (PELs) - Table Z1	paraffinic distillate, heavy, hydrotreated (severe)	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available

#### **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
paraffinic distillate, heavy, hydrotreated (severe)	2,500 mg/m3		Not Available	
paraffinic distillate, heavy, solvent- refined (severe)	Not Available		Not Available	
nonylated diphenylamines	Not Available		Not Available	

#### Exposure controls

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

# Personal protection











## Eye and face protection

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

## Skin protection

See Hand protection below

# Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## choice.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

Personal hygiene is a key element of effective hand care.

- Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

## **Body protection**

See Other protection below

Other protection

- Overalls.
- P.V.C. apron. Barrier cream.

# Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

<sup>^ -</sup> Full-face

Chemwatch: **51-87120** Page **5** of **9** 

Version No: 2.1.1.1

# 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

Issue Date: **15/08/2019**Print Date: **20/08/2019** 

chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	Brown liquid with characteristic odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.846
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-42	Viscosity (cSt)	38 @ 40C, 7.18 @ 100C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	220	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

# Information on toxicological effects

•	
Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  Inhalation hazard is increased at higher temperatures.  Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.  Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.  Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.  Open cuts, abraded or irritated skin should not be exposed to this material  The material may accentuate any pre-existing dermatitis condition  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet.  Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin.

Chemwatch: 51-87120 Page 6 of 9 Issue Date: 15/08/2019 Version No: 2.1.1.1

# 20324, 20328 SPECIAL TEC

C AA 0W-16 1L, 5L	Print Date: 20/08/2019

20324, 20328 SPECIAL TEC AA	TOXICITY	IRRITATION	
0W-16 1L, 5L	Not Available	Not Available	
	TOXICITY	IRRITATION	
paraffinic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no advers	e effect observed (not irritating) <sup>[1]</sup>
hydrotreated (severe)	Inhalation (rat) LC50: >5.3 mg/l4 h <sup>[1]</sup>	Skin: no advers	se effect observed (not irritating) <sup>[1]</sup>
	Oral (rat) LD50: >2000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
paraffinic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: no advers	e effect observed (not irritating) <sup>[1]</sup>
solvent-refined (severe)	Inhalation (rat) LC50: >5.3 mg/l4 h <sup>[1]</sup>	Skin: no advers	se effect observed (not irritating) <sup>[1]</sup>
	Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
nonylated diphenylamines	Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>	Eye: no advers	e effect observed (not irritating) <sup>[1]</sup>
		Skin: no advers	se effect observed (not irritating) <sup>[1]</sup>
HEAVY, SOLVENT-REFINED (SEVERE)	No significant acute toxicological data identified in litera		Direction to the second
	No significant acute toxicological data identified in litera	ture search.	
NONYLATED DIPHENYLAMINES	slight to very low order of toxicity following oral or topica	Overexposure may cause skin and airw I administration.	ay irritation with dizziness and flu-like symptoms. All show a
PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE) & PARAFFINIC DISTILLATE, HEAVY, SOLVENT- REFINED (SEVERE)	*	ersely related to the severity or extent of ciated with undesirable components, an inversely related to the degree of process or extent of processing will have similar expendent of the degree of processing the distillate base oils is inversely related the distillate base oils is inversely related the highest levels of undesirable component mutation-causing activities. Highly arming undesirable components.  Vkg body weight and the semilethal dosvirals have varied from "non-irritating" to	of processing the oil has undergone, since: d sing; toxicities; ne oil receives. d to the degree of processing. ents, have the largest variation of hydrocarbon molecules nd severely refined distillate base oils are produced from e by skin contact is >2g/kg body weight. The semilethal
	Evidence of carolinegerilotty may be inadequate of limite	d in animal testing.	
Acute Toxicity			v
Acute Toxicity Skin Irritation/Corrosion	X X	Carcinogenicity  Reproductivity	×

Legend:

STOT - Single Exposure

Aspiration Hazard

STOT - Repeated Exposure

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

Mutagenicity

Serious Eye Damage/Irritation

Respiratory or Skin sensitisation

×

# Toxicity

20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>100mg/L	2
paraffinic distillate, heavy, hydrotreated (severe)	EC50	48	Crustacea	>10-mg/L	2
	EC50	96	Algae or other aquatic plants	>1000mg/L	1
	NOEC	504	Crustacea	>1mg/L	1

Chemwatch: 51-87120 Page 7 of 9

Version No: 2.1.1.1

## 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

Issue Date: **15/08/2019** Print Date: **20/08/2019** 

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>100mg/L	2
paraffinic distillate, heavy, solvent-refined (severe)	EC50	48	Crustacea	>10-mg/L	2
contain rainiaa (catara)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
	NOEC	504	Crustacea	>1mg/L	1
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>100mg/L	2
nonylated diphenylamines	EC50	48	Crustacea	51mg/L	2
	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	96	Crustacea	<10mg/L	1

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

## **Bioaccumulative potential**

Ingredient	Bioaccumulation
	No Data available for all ingredients

# Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

## **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Product / Packaging disposal

  Where in doubt contact the responsible authority.

  Posted wherever possible or consult manufacture.
  - ▶ Recycle wherever possible or consult manufacturer for recycling options.
  - Consult State Land Waste Authority for disposal.
  - ► Bury or incinerate residue at an approved site.
  - Recycle containers if possible, or dispose of in an authorised landfill.

# **SECTION 14 TRANSPORT INFORMATION**

# **Labels Required**

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

PARAFFINIC DISTILLATE, HEAVY, HYDROTREATED (SEVERE)(64742-54-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemwatch: 51-87120 Page 8 of 9 Issue Date: 15/08/2019 Version No: 2.1.1.1 Print Date: 20/08/2019

20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air containing at least 99% by weight of components already assessed by IMO Contaminants International Agency for Research on Cancer (IARC) - Agents Classified by the IARC US - Washington Permissible exposure limits of air contaminants Monographs US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants International FOSFA List of Banned Immediate Previous Cargoes US ACGIH Threshold Limit Values (TLV) US - Alaska Limits for Air Contaminants US ACGIH Threshold Limit Values (TLV) - Carcinogens US - California Permissible Exposure Limits for Chemical Contaminants US AIHA Workplace Environmental Exposure Levels (WEELs) US - Hawaii Air Contaminant Limits US Chemical Footprint Project - Chemicals of High Concern List US - Idaho - Limits for Air Contaminants US Department of Transportation (DOT) Marine Pollutants - Appendix B US - Idaho Toxic Air Pollutants Non- Carcinogenic Increments - Occupational Exposure Limits US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk US - Michigan Exposure Limits for Air Contaminants Liquid Cargoes US - Minnesota Permissible Exposure Limits (PELs) US NIOSH Recommended Exposure Limits (RELs) US - Oregon Permissible Exposure Limits (Z-1) US OSHA Permissible Exposure Levels (PELs) - Table Z1 US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID) US - Pennsylvania - Hazardous Substance List Number US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants US TSCA Chemical Substance Inventory - Interim List of Active Substances

## PARAFFINIC DISTILLATE, HEAVY, SOLVENT-REFINED (SEVERE)(64741-88-4.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Chemical Footprint Project - Chemicals of High Concern List	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US Postal Service (USPS) Numerical Listing of Proper Shipping Names by Identification (ID)	US TSCA Chemical Substance Inventory - Interim List of Active Substances
Number	

#### NONYLATED DIPHENYLAMINES(36878-20-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

IMO IBC Code Chapter 17: Summary of minimum requirements	US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk	US TSCA Chemical Substance Inventory - Interim List of Active Substances

## **Federal Regulations**

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No	)
Gas under pressure	No	)
Explosive	No	)
Self-heating	No	)
Pyrophoric (Liquid or Solid)	No	)
Pyrophoric Gas	No	)
Corrosive to metal	No	)
Oxidizer (Liquid, Solid or Gas)	No	)
Organic Peroxide	No	)
Self-reactive	No	)
In contact with water emits flammable gas	No	)
Combustible Dust	No	)
Carcinogenicity	No	)
Acute toxicity (any route of exposure)	No	)
Reproductive toxicity	No	)
Skin Corrosion or Irritation	No	)
Respiratory or Skin Sensitization	No	)
Serious eye damage or eye irritation	No	)
Specific target organ toxicity (single or repeated exposure)	Yes	S
Aspiration Hazard	No	)
Germ cell mutagenicity	No	)
Simple Asphyxiant	No	)
Hazards Not Otherwise Classified	No	)

## US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

# **State Regulations**

# US. CALIFORNIA PROPOSITION 65

None Reported

# **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (paraffinic distillate, heavy, hydrotreated (severe); nonylated diphenylamines; paraffinic distillate, heavy, solvent-refined (severe))
China - IECSC	Yes

Chemwatch: 51-87120 Page 9 of 9 Issue Date: 15/08/2019 Version No: 2.1.1.1 Print Date: 20/08/2019

# 20324, 20328 SPECIAL TEC AA 0W-16 1L, 5L

Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (nonylated diphenylamines)
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Thailand - TECI	No (paraffinic distillate, heavy, hydrotreated (severe); nonylated diphenylamines; paraffinic distillate, heavy, solvent-refined (severe))
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## **SECTION 16 OTHER INFORMATION**

Revision Date	15/08/2019
Initial Date	15/08/2019

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.