

Snowbike Motor Oil SAE 0W-40

Description

Fully synthetic low-friction motor oil designed for quick lubrication on cold start. The combination of high quality synthetic base oils together with an advanced additive package produces a low viscosity motor oil with high shear stability. This high-quality blend prevents engine deposits. Engine wear is reduced to a minimum thanks to low friction and heat.

Properties

- excellent wear protection
- outstanding high temperature stability
- extremely low evaporation loss
- instant lubrication after cold start
- outstanding lubrication reliability
- optimum oil pressure under all operating conditions
- outstanding engine cleanliness
- tested for the use with catalytic converters

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

JASO MA2

Technical data

SAE class (engine oils)	0W-40 SAE J300
Density at 59 °F	0,845 g/cm ³ DIN 51757
Viscosity at 104 °F	76,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	13,7 mm ² /s ASTM D 7042-04
Viscosity at -31 °F (CCS)	<6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
Pour point	-44 °F DIN ISO 3016
Flash point	439 °F DIN ISO 2592
Evaporation loss (Noack)	13,0 % ASTM D 5800-08 Method B
Total base number	6,4 mg KOH/g DIN ISO 3771
Color number (ASTM)	L 2,0 DIN ISO 2049



Areas of application

For 4-stroke Snowbike engines, with or without a wet clutch, when a motor oil equivalent to current specifications is required or recommended. Safe with catalytic converters.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Comment



WARNING: Reproductive Harm - www.P65Warnings.ca.gov

Available pack sizes

1 l Canister plastic	20356 USA AND CANADA (-EN-F-)
4 l Canister plastic	20358 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.