

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L Liqui Moly GmbH

Chemwatch: 5430-44 Version No: 2.1.1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 26/10/2020 Print Date: 27/10/2020 S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L	
Synonyms	Not Available	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Liqui Moly GmbH
Address	Jerg-Wieland-Strasse 4 Ulm D-89081 Germany
Telephone	+49 731 1420 0
Fax	+49 731 1420 82
Website	http://www.liqui-moly.com/
Email	Not Available

Emergency phone number

Association / Organisation	INFOTRAC
Emergency telephone numbers	+1800 535 5053 (US, Canada & Mexico)
Other emergency telephone numbers	+1 352 323 3500 (International)

SECTION 2 Hazard(s) identification

Classification of the substance or mixture





Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Eye Irritation Category 2A, Skin Sensitizer Category 1, Acute Aquatic Hazard Category 3

Label elements

Hazard pictogram(s)



Signal word Warning

Hazard statement(s)

H319	Causes serious eye irritation.	
H317	May cause an allergic skin reaction.	
H402	Harmful to aquatic life.	

Chemwatch: **5430-44** Page **2** of **10**

Version No: 2.1.1.1

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: 26/10/2020 Print Date: 27/10/2020

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P261	Avoid breathing mist/vapours/spray.	
P273	oid release to the environment.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).	
P363	Wash contaminated clothing before reuse.	
P302+P352	IF ON SKIN: Wash with plenty of water and soap.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name	
64741-88-4.	>60	paraffinic distillate, heavy, solvent-refined (severe)	
72623-87-1.	20-40	lubricating oils, petroleum C20-50, hydrotreated neutral	
68784-31-6	1-5	zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate	
722503-69-7	1-5	methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium	
722503-68-6	<1	methyl-C20-24-alkylbenzenesulfonic acid. branched, calcium	

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically

- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

SECTION 5 Fire-fighting measures

Extinguishing media

► Foam

Chemwatch: 5430-44 Page 3 of 10

Version No: 2.1.1.1 20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: 26/10/2020 Print Date: 27/10/2020

- Dry chemical powder
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus
- Prevent, by any means available, spillage from entering drains or water course.
- ▶ Use water delivered as a fine spray to control fire and cool adjacent area.

- ▶ Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:

Fire/Explosion Hazard

carbon dioxide (CO2) phosphorus oxides (POx) sulfur oxides (SOx)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes. May emit corrosive fumes

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills

Slippery when spilt

- Remove all ignition sources
- Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes
- ▶ Control personal contact with the substance, by using protective equipment.

Major Spills

Slippery when spilt Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Hydrogen sulfide (H2S or Sour Gas) may be present when loading and unloading transport vessels. Stay upwind and away from newly opened hatches and allow to vent thoroughly before handling material. Steam may be used to vent hatches. Keep all sources of ignition away from loading area.

Safe handling

▶ DO NOT allow clothing wet with material to stay in contact with skin

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs
- Use in a well-ventilated area
- Prevent concentration in hollows and sumps

Other information

- Store in original containers.
- Keep containers securely sealed. No smoking, naked lights or ignition sources.
- ▶ Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container

- Metal can or drum
- Packaging as recommended by manufacturer
- Check all containers are clearly labelled and free from leaks.

Storage incompatibility

CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.

► Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Chemwatch: 5430-44 Page 4 of 10

Version No: 2.1.1.1

Issue Date: 26/10/2020 Print Date: 27/10/2020 20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	lubricating oils, petroleum C20-50, hydrotreated neutral	Heavy mineral oil mist, Paraffin oil mist, White mineral oil mist	5 mg/m3	10 mg/m3	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	lubricating oils, petroleum C20-50, hydrotreated neutral	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	lubricating oils, petroleum C20-50, hydrotreated neutral	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m3	Not Available	Not Available	URT irr

Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lubricating oils, petroleum C20-50, hydrotreated neutral	Mineral oil, heavy or light; (paraffin oil; Deobase, deodorized; heavy paraffinic; heavy naphthenic); distillates; includes 64741-53-3, 64741-88-4, 8042-47-5, 8012-95-1; 64742-54-7	140 mg/m3	1,500 mg/m3	8,900 mg/m3

Ingredient	Original IDLH	Revised IDLH
paraffinic distillate, heavy, solvent-refined (severe)	Not Available	Not Available
lubricating oils, petroleum C20-50, hydrotreated neutral	2,500 mg/m3	Not Available
zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate	Not Available	Not Available
methyl-C20-26- alkylbenzenesulfonic acid, branched, calcium	Not Available	Not Available
methyl-C20-24- alkylbenzenesulfonic acid, branched, calcium	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
methyl-C20-26- alkylbenzenesulfonic acid, branched, calcium	E	≤ 0.01 mg/m³
methyl-C20-24- alkylbenzenesulfonic acid, branched, calcium	D	> 0.01 to ≤ 0.1 mg/m³
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection









Eye and face protection

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

See Hand protection below

- ▶ Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care.

Body protection

Hands/feet protection

See Other protection below

Other protection

- Overalls.
- ▶ P.V.C apron. Barrier cream.
- Skin cleansing cream.

Chemwatch: **5430-44**Version No: **2.1.1.1**

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: **26/10/2020**Print Date: **27/10/2020**

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

 $A(All \ classes) = Organic \ vapours, \ B \ AUS \ or \ B1 = Acid \ gasses, \ B2 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ B3 = Acid \ gas \ or \ hydrogen \ cyanide(HCN), \ E = Sulfur \ dioxide(SO2), \ G = Agricultural \ chemicals, \ K = Ammonia(NH3), \ Hg = Mercury, \ NO = Oxides \ of \ nitrogen, \ MB = Methyl \ bromide, \ AX = Low \ boiling \ point \ organic \ compounds(below 65 \ degC)$

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Brown liquid with characteristic odour; not miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	0.865
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-36	Viscosity (cSt)	94 @ 40C, 14.5 @ 100C
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	230	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Inhalation hazard is increased at higher temperatures. Not normally a hazard due to non-volatile nature of product Inhalation of oil droplets or aerosols may cause discomfort and may produce chemical inflammation of the lungs.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Repeated exposure may cause skin cracking, flaking or drying following normal handling and use. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material The material may accentuate any pre-existing dermatitis condition Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Chemwatch: **5430-44** Page **6** of **10**

Version No: 2.1.1.1

METHYL-C20-26-

& METHYL-C20-24-

ALKYLBENZENESULFONIC

ACID, BRANCHED, CALCIUM

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: **26/10/2020**Print Date: **27/10/2020**

Eve This material can cause eye irritation and damage in some persons Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts Chronic Prolonged or repeated skin contact may cause degreasing, followed by drying, cracking and skin inflammation. Oil may contact the skin or be inhaled. Extended exposure can lead to eczema, inflammation of hair follicles, pigmentation of the face and warts on the soles of the feet. 20506, 20508, 20496, 20497, TOXICITY IRRITATION 20498 MARINE 4T MOTOR OIL Not Available Not Available 10W-40 1L, 4L, 20L, 60L, 205L TOXICITY IRRITATION paraffinic distillate, heavy. Oral (rat) LD50: >5000 mg/kg[2] Eye: no adverse effect observed (not irritating)[1]solvent-refined (severe) Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION lubricating oils, petroleum Oral (rat) LD50: >5000 mg/kg[1] Eye: no adverse effect observed (not irritating)[1]C20-50, hydrotreated neutral Skin: no adverse effect observed (not irritating)[1] TOXICITY IRRITATION zinc bis(sec-butvl and Oral (rat) LD50: 2900 mg/kg^[1] Eye: adverse effect observed (irritating)[1] 1.3-dimethylbutyl) dithiophosphate Skin: no adverse effect observed (not irritating)^[1] methyl-C20-26-TOXICITY IRRITATION alkylbenzenesulfonic acid, Not Available Not Available branched, calcium methyl-C20-24-TOXICITY IRRITATION alkylbenzenesulfonic acid, Not Available Not Available branched, calcium Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances PARAFFINIC DISTILLATE, The substance is classified by IARC as Group 3: **HEAVY, SOLVENT-REFINED** NOT classifiable as to its carcinogenicity to humans. (SEVERE) Evidence of carcinogenicity may be inadequate or limited in animal testing The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis ZINC BIS(SEC-BUTYL AND Dithiophosphate alkyl esters is corrosive and toxic to the tissues on skin or oral exposure depending on its concentration. Symptoms included 1,3-DIMETHYLBUTYL) diarrhoea, skin and gastrointestinal irritation, lethargy, reduced food intake, staining about the nose and eye; occasionally, there was drooping of DITHIOPHOSPHATE the eyelid, hair standing up, inco-ordination and salivation. Toxicity is reduced following inhalation (due to vapour pressure and high viscosity). It may produce reproductive, developmental and genetic toxicity on experimental animals, but no substantive data is available to establish effect on humans PARAFFINIC DISTILLATE, HEAVY, SOLVENT-REFINED (SEVERE) & ZINC BIS(SEC-BUTYL AND 1,3-DIMETHYLBUTYL) **DITHIOPHOSPHATE &** No significant acute toxicological data identified in literature search. METHYL-C20-26-**ALKYLBENZENESULFONIC** ACID, BRANCHED, CALCIUM & METHYL-C20-24-**ALKYLBENZENESULFONIC** ACID, BRANCHED, CALCIUM The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: The adverse effects of these materials are associated with undesirable components, and The levels of the undesirable components are inversely related to the degree of processing; Distillate base oils receiving the same degree or extent of processing will have similar toxicities; The potential toxicity of residual base oils is independent of the degree of processing the oil receives. The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. PARAFFINIC DISTILLATE, Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon HEAVY, SOLVENT-REFINED molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils (SEVERE) & LUBRICATING are produced from unrefined and mildly refined oils by removing or transforming undesirable components. In comparison to unrefined and mildly OILS, PETROLEUM C20-50, refined base oils, the highly and severely refined distillate base oils have a smaller range of hydrocarbon molecules and have demonstrated very HYDROTREATED NEUTRAL low mammalian toxicity. Testing of residual oils for mutation-causing and cancer-causing potential has shown negative results, supporting the belief that these materials lack biologically active components or the components are largely non-bioavailable due to their molecular size. Toxicity testing has consistently shown that lubricating base oils have low acute toxicities. For highly and severely refined distillate base oils: In animal studies, the acute, oral, semilethal dose is >5g/kg body weight and the semilethal dose by skin contact is >2g/kg body weight. The semilethal concentration for inhalation is 2.18 to >4 mg/L. The materials have varied from "non-irritating" to "moderately irritating" when tested for skin and eye irritation. Testing for sensitisation has been negative.

The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact

involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the

eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria

Chemwatch: **5430-44** Version No: **2.1.1.1**

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: **26/10/2020**Print Date: **27/10/2020**

ALKYLBENZENESULFONIC ACID, BRANCHED, CALCIUM

distribution of the substance and the opportunities for contact with it are equally important.

For alkaryl sulfonate petroleum additives:

Acute toxicity: Existing data indicates relatively low acute toxicity. Animal testing suggested diarrhea and reduced food intake, which is consistent with the detergents in an oil-based vehicle having an irritating effect on the gastrointestinal tract.

Subchronic toxicity: Existing data suggests minimal toxicity after chronic exposure by mouth. Repeated skin contact and inhalation in animals caused injury to the skin and the lungs, respectively.

Reproductive and Developmental Toxicity: Existing data did not show this group of substances to cause reproductive or developmental toxicity. Linear alkyl benzene sulfonates are derived from strong corrosive acids. Animal testing has shown they can cause skin reactions, eye irritation, sluggishness, passage of frequent watery stools, weakness and may lead to death. They may also react with surfaces of the mouth and intestines, depending on the concentration exposed to. There is no evidence of harm to the unborn baby or tendency to cause cancer.

Acute Toxicity	×	Carcinogenicity	X
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	x

Legend:

💢 – Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 Ecological information

Toxicity

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>100mg/L	2
paraffinic distillate, heavy, solvent-refined (severe)	EC50	48	Crustacea	>10-mg/L	2
Solvent reimod (Severe)	EC50	96	Algae or other aquatic plants	>1000mg/L	1
	NOEC	504	Crustacea	>1mg/L	1
	Endpoint	Test Duration (hr)	Species	Value	Source
lubricating oils, petroleum	LC50	96	Fish	>100mg/L	2
C20-50, hydrotreated neutral	EC50	48	Crustacea	>10-mg/L	2
	NOEC	504	Crustacea	>1mg/L	1
	Endpoint	Test Duration (hr)	Species	Value	Source
zinc bis(sec-butyl and	LC50	96	Fish	4.4mg/L	2
1,3-dimethylbutyl)	EC50	48	Crustacea	75mg/L	2
dithiophosphate	EC50	72	Algae or other aquatic plants	240mg/L	2
	NOEC	504	Crustacea	0.4mg/L	2
methyl-C20-26- alkylbenzenesulfonic acid, branched, calcium	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
methyl-C20-24- alkylbenzenesulfonic acid, branched, calcium	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Availabl

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suitt V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Harmful to aquatic organisms.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Page 8 of 10

Version No: 2.1.1.1 20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L Issue Date: 26/10/2020 Print Date: 27/10/2020

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Product / Packaging disposal

▶ Reduction Reuse

- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- · Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

paraffinic distillate, heavy, solvent-refined (severe) is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

lubricating oils, petroleum C20-50, hydrotreated neutral is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs US ACGIH Threshold Limit Values (TLV)

US NIOSH Recommended Exposure Limits (RELs) US OSHA Permissible Exposure Levels (PELs) - Table Z1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate is found on the following regulatory lists

US CWA (Clean Water Act) - Priority Pollutants US CWA (Clean Water Act) - Toxic Pollutants US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium is found on the following regulatory lists

methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium is found on the following regulatory lists

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)

Nο

Version No: **2.1.1.1**

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: 26/10/2020 Print Date: 27/10/2020

Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

None Reported

National Inventory Status

National Inventory	Status
Australia - AIIC	No (methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Australia - Non-Industrial Use	No (paraffinic distillate, heavy, solvent-refined (severe); lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Canada - DSL	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Canada - NDSL	No (paraffinic distillate, heavy, solvent-refined (severe); lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
China - IECSC	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Europe - EINEC / ELINCS / NLP	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Japan - ENCS	No (lubricating oils, petroleum C20-50, hydrotreated neutral; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Korea - KECI	No (zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24 alkylbenzenesulfonic acid, branched, calcium)
New Zealand - NZIoC	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Philippines - PICCS	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
USA - TSCA	No (methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Taiwan - TCSI	Yes
Mexico - INSQ	No (lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Vietnam - NCI	No (zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium)
Russia - ARIPS	No (lubricating oils, petroleum C20-50, hydrotreated neutral; zinc bis(sec-butyl and 1,3-dimethylbutyl) dithiophosphate; methyl-C20-26-alkylbenzenesulfonic acid, branched, calcium; methyl-C20-24-alkylbenzenesulfonic acid, branched, calcium)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets,

SECTION 16 Other information

Revision Date	26/10/2020
Initial Date	26/10/2020

Chemwatch: **5430-44** Page **10** of **10**

Version No: 2.1.1.1

20506, 20508, 20496, 20497, 20498 MARINE 4T MOTOR OIL 10W-40 1L, 4L, 20L, 60L, 205L

Issue Date: **26/10/2020**Print Date: **27/10/2020**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average PC—STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.