Product information

Top Tec 6200 SAE 0W-20



Description

Fully synthetic superior low friction motor oil. Specifically developed for the high requirements of select Volkswagen and Audi vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. The innovative additive technology ensures excellent protection against wear, superb engine cleanness and greater oxidation stability. Use with extended oil change intervals as per manufacturer.

Properties

- excellent cold-start behavior
- excellent wear resistance
- highest fuel economy
- promotes quick engine start
- outstanding resistance to oxidation
- added protection with E10 fuels
- increases operational reliability
- compatible for the use with turbochargers and catalytic converters

Specifications and approvals:

VW 508 00 • VW 509 00

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ACEA C5 • Porsche C20

Technical data

SAE Viscosity 0W-20 SAE J300 Density at 59 °F 0,845 g/cm³

DIN 51757

Viscosity at 104 °F 40,0 mm²/s ASTM D 7042-04

Viscosity at 212°F 8,1 mm²/s

ASTM D 7042-04

Viscosity at -40 °F (MRV) < 60000 mPas

ASTM D 4684

Viscosity at -31 °F (CCS) ≤ 6200 mPas

ASTM D 5293

Viscosity index 180

DIN ISO 2909

HTHS at 302 °F ≥ 2,6 mPas

ASTM D 5481

Pour point -49 °F

DIN ISO 3016



Technical data

Evaporation loss (Noack) 10,5 %

CEC-L-40-A-93

Total base number 9,2 mg KOH/g

DIN ISO 3771

Flash point 428 °F

DIN ISO 2592

Sulfate ash $\leq 0.8 \%$

DIN 51575

Color / appearance grün

Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers. **Not backwards compatible.**

Application

Observe the manufacturers instructions!

Available pack sizes

1 l Canister plastic 20236

USA AND CANADA (-EN-

F-)

5 l Canister plastic 20238

USA AND CANADA (-EN-

F-)

205 l Drum sheet metal 22089

USA AND CANADA (-EN-

F-)

1000 l Container 22164

USA AND CANADA (-EN-

F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871

www.liqui-moly.de