## **Product information**

# Top Tec MTF 5100 SAE 75W



#### **Description**

Low-viscosity high-performance transmission fluid. High shear stability provides low fuel consumption and excellent wear protection. Outstanding resistance to viscosity breakdown provides superior shift performance in all operating conditions. Suitable for a variety of transmissions.

## **Properties**

- outstanding shifting comfort under all operating conditions
- guarantees low fuel consumption
- excellent shear stability
- excellent wear resistance
- outstanding corrosion protection
- excellent viscosity/temperature properties
- proper synchronizer function
- outstanding resistance to oxidation

## Specifications and approvals:

API GL4

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW 83 22 7 533 818 • BMW MTF LT-3 • Fiat 9.55550-MZ6 • Ford WSS-M2C 200-D2 • Toyota • VW G 052 178 • VW G 052 512 • VW G 052 726 • VW G 055 512 • VW G 060 726 • VW G 070 726

#### **Technical data**

SAE class (gear oils) 75W

**SAE J 306** 

Density at 59 °F 0,860 g/cm<sup>3</sup>

DIN 51757

Viscosity at 104 °F 33,1 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at 212°F 6,0 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -40 °F (Brook- < 150000 mPas field) ASTM D 2983-09

Viscosity index 130

**DIN ISO 2909** 

Pour point -44 °F

**DIN ISO 3016** 

Flash point 435 °F

**DIN ISO 2592** 

Color number (ASTM) L 2.5

**DIN ISO 2049** 

### Areas of application

Universal use in modern gearboxes and specific dualclutch transmissions (DCT). Suitable for numerous BMW and Volkswagen / Audi vehicles as well as for transmissions from other manufacturers where a gear oil meeting current product specification is required or recommended.

#### **Application**

Observe the manufacturers instructions!

### Available pack sizes

1 l Can plastic 20352

USA AND CANADA (-EN-

F-)

20 l Canister plastic 20354

USA AND CANADA (-EN-

F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Postfach 2829 89018 Ulm Germany Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de