

Motorbike Shock Absorber Oil VS RACE

Description

Fully synthetic shock absorber oil. Prevents deposit build-up while reducing friction and wear. Foaming is prevented even during extreme conditions. The unique formulation allows better handling and rider feedback which allows easier suspension tuning. Fluid color is blue.



Properties

- increases driving safety
- very wear resistant
- outstanding viscosity stability
- prevents the build-up of deposits
- very compatible with seals
- outstanding corrosion protection
- prevents foam formation

Available pack sizes

1 l Can plastic	20290 USA AND CANADA (-EN-F-)
20 l Canister plastic	20292 USA AND CANADA (-EN-F-)

Technical data

Density at 59 °F	0,825 g/cm ³ DIN 51757
Viscosity at 104 °F	17,4 mm ² /s ASTM D 7042-04
Viscosity at 212°F	3,95 mm ² /s ASTM D 7042-04
Viscosity index	124 DIN ISO 2909
Demulgation characteristics at 129 °F	< 20 min DIN ISO 6614
Pour point	-81 °F DIN ISO 3016
Flash point	428 °F DIN ISO 2592
Color / appearance	blau / blue

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Designed for racing or extreme motorbike and power-sports use and when a fluid according to current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted. Professional use only.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov