

Marine Winch Grease

Description

A synthetic high-performance grease enhanced with solid PTFE solid-lubricants. Specifically developed for use on winches and hoists. The solid lubricant provides the ultimate in wear protection and reduces friction. Resistant to seawater and freshwater and with excellent adhesive properties. Does not contain resins or acids and does not affect plastics. Certification acc DIN KHCF1N-35.



Properties

- excellent high-pressure and wear protection properties
- extremely adherent
- outstanding sea and fresh water resistance
- ensures a long service life

Technical data

Brief description	KHCF1N-35
Saponification type	gel
Base	Syntheseöl / synthetic oil
Operating temperature range	-95 bis 302 °F
Color / appearance	weiß / white
NLGI number	1 DIN 51 818
Dropping point	ohne/without DIN ISO 2176
Base oil viscosity 104 °F	440 mm ² /s DIN 51 562
resistance to water washout	0 DIN 51807

Areas of application

Particularly suited for winches and hoists with non-ferrous metal pairings and plastic/metal pairings. Saltwater resistant.

Application

Observe the manufacturers instructions!

Available pack sizes

100 g Tube plastic	20524 USA AND CANADA (-EN-F-)
--------------------	----------------------------------

Our information is based on thorough research and may be considered reliable, although not legally binding.