

Marine High Performance Gear Oil SAE 85W-90

Description

Fully synthetic high-performance gear oil with extreme performance reserves. Provides accurate transmission function in extreme operating conditions and when exposed to large temperature fluctuations. Meets or exceeds the requirements and specifications of major transmission manufacturers.

Properties

- outstanding corrosion protection
- high pressure-absorption capability
- excellent viscosity/temperature properties
- slows oil degradation and stabilizes viscosity
- excellent high-pressure and wear protection properties

Technical data

SAE class (gear oils)	85W-90 SAE J 306
Density at 59 °F	0,880 g/cm ³ DIN 51757
Viscosity at 104 °F	163,5 mm ² /s ASTM D 7042-04
Viscosity at 212°F	15,5 mm ² /s ASTM D 7042-04
Viscosity at 10 °F (Brookfield)	<= 150000 mPas ASTM D 2983-05
Viscosity index	96 DIN ISO 2909
Pour point	-17 °F DIN ISO 3016
Flash point	435 °F DIN ISO 2592
Color / appearance	blau / blue

Areas of application

For transmissions where a high-performance gear lube with current product specifications is required or recommended.

Application

Observe the manufacturers instructions!

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov



Available pack sizes

1 l Can plastic	20536 USA AND CANADA (-EN-F-)
20 l Canister plastic	20492 USA AND CANADA (-EN-F-)
60 l Drum sheet metal	20493 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.