

# Product information

## Motorbike Speed Additive

PI 38/26/08/2020



### Description

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

### Properties

- increased performance
- improves the acceleration
- protects fuel against oxidation and aging
- cleans the fuel system
- prevents corrosion
- prevents carburetor icing
- increases operational reliability

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb, klar / yellow, clear
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	<7 mm <sup>2</sup> /s
Density at 68 °F	0,814 g/cm <sup>3</sup>
Hazard class as per German VbF	A III
Flash point	>142 °F

### Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

### Application

Contents (150 mL) is sufficient for 15–20 Liters (4 gal. to 5.3 gal.) gasoline. Add at every fill-up.

### Comment

 **WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



### Available pack sizes

150 ml Can sheet metal	20108 USA (-EN-)
150 ml Can sheet metal	22104 CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**