Product information

Motorbike Gasoline Stabilizer



Description

Preserves fuel against premature aging and oxidation during long term storage. Prevents corrosion in fuel system and increases operational reliability of 2- and 4-stroke engines in motor scooters, ATVs, snowmobiles etc. during long-term storage.

Properties

- has a lasting effect
- increases operational reliability
- simple to use
- tested for the use with catalytic converters
- cost-effective due to exact dosage
- protects fuel against oxidation and aging

Technical data

Base Additiv-Kombination in

Trägerflüssigkeit /

additive mixture in carrier

liquid

A III

Color / appearance blau / blue

Odor charakteristisch /

characteristic

Form flüssig / liquid
Density at 59 °F 0,822 g/cm³

Denisity at 37 1 0,022 g/ci

Hazard class as per Ger-

man VbF

Flash point >142 °F Viscosity at 104 °F <7 mm²/s

Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

Application

Use 25 mL dosage with 5 Liters (1.3 gal.) of fuel. Add to fuel and let the engine idle for approx. 10 minutes.

Comment

WARNING: Cancer - www.P65Warnings.ca.gov



Available pack sizes

250 ml Dispensing bottle 20052 plastic USA (-EN-)

250 ml Dispensing bottle 22102

plastic CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.