

Product information

Motorbike 2T Synth Offroad Race

PI 26/26/08/2020



Description

Fully synthetic high-performance 2-stroke motor oil developed and tested on racing machines. Ensures maximum performance and protection of the engine in all operating conditions. Outstanding lubrication and engine cleanliness, excellent friction behavior and minimized wear as well as less smoke. This oil improves the riding experience!

Properties

- very wear resistant
- prevents the build-up of deposits
- residue-free combustion
- high thermal stability
- good corrosion protection
- self mixing

Specifications and approvals:

API TC • Husqvarna • ISO L-EGD • JASO FD

Technical data

Density at 59 °F	0,875 g/cm ³ DIN 51757
Viscosity at 104 °F	50 mm ² /s ASTM D 7042-04
Viscosity at 212°F	9,1 mm ² /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	208 °F DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	rot / red

Areas of application

For air or water cooled 2-stroke gasoline engines where an oil according to current product specifications is required or recommended. Self-mixing. Pre-mix applications up to 1:100 ratio and according to the manufacturers instructions.



Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used in undiluted form.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

1 l Canister plastic	20178 USA AND CANADA (-EN-F-)
4 l Canister plastic	20180 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.