Product information

Brake Anti-Squeal Paste



Description

A synthetic based specialty with a solid agent to prevent and eliminate noise from brake pads. It is extremely adhesive and high temperature resistant, it resists road salt and water wash-out. With excellent corrosion protection and particularly suited for use with aluminum and magnesium materials as well as on vehicles with ABS/ESP systems.

Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- extremely adherent
- ideally suited as a separating paste

Technical data

Form pastös, flüssig /

pastelike,liquid

Color / appearance blau / blue

Base synthetische u.

keramische Wirkstoffe

Operating temperature

range

-40 bis 392 kurzfristig bis 482 / -40 to 392 short

term 482 °F

als Schmierpaste / as lubricating agent

-40 bis 2192 / -40 to 2192

°F

als Trennpaste / as release agent

Flash point >410 °F

Odor schwach / slightly

Shelf life in original sealed 24 months

container

Areas of application

Suitable for use in most common disk brake systems. Must never be applied to the friction surface of the brake disc / brake pads.

Application

Clean the surfaces thoroughly before use and then apply to the back of the brake pad and to the contact surfaces and fasteners. Do not apply on friction surfaces!



Comment

Do not under any circumstances allow Brake Anti-Squeal Paste to get onto the friction surface of the brake lining or the brake disc.

part no. 20240: **WARNING:** Cancerwww.P65Warnings.ca.gov

Available pack sizes

200 ml Can aerosol 20240

USA (-EN-)

250 g Brush-in-cap can sheet metal

22092 USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.