

## Motorbike Fork Oil SAE 7,5W medium/light

### Description

Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum drivability and damping.

### Properties

- good corrosion protection
- prevents seals from swelling
- prevents foam formation
- high wear resistance
- increases driving safety

### Technical data

Density at 59 °F	0,825 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	22,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	4,75 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	139 DIN ISO 2909
Pour point	-65 °F DIN ISO 3016
Flash point	453 °F DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

### Available pack sizes

1 l Can plastic	20098 USA AND CANADA (-EN-F-)
20 l Canister plastic	20403 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheeled vehicles.

### Application

Follow the instructions of the telescopic fork, shock absorber and two-wheeled vehicle manufacturers.