

Radiator Stop Leak

Description

Will immediately seal small leaks caused by external damage, porous solder joints and hairline cracks in cooling systems of all water cooled engines. Coolant is prevented from entering the combustion chamber due to internal leaks from head gasket etc. It does not react with oxygen or heat and will never prevent system flow or cause overheating. Radiator Stop Leak works as long as it's in the coolant.

Properties

- compatible with most types of coolant or anti-freeze
- Safe to use with aluminum radiators
- permanently seals smaller leaks
- will not affect water pump or heater unit
- use as preventive

Technical data

| | |
|---------------------|----------------------------|
| Form | flüssig / liquid |
| Color / appearance | weiß, trüb / white, cloudy |
| Density at 68 °F | 1,05 g/cm ³ |
| Solubility in water | mischbar / mixable |
| Odor | schwach / weak |
| Flash point | >212 °F |

Available pack sizes

| | |
|------------------------|--------------------------|
| 250 ml Can sheet metal | 20132 USA (-EN-) |
| 250 ml Can sheet metal | 20332 CANADA (-EN-F-) |

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Used for sealing small leaks in cooling circuits of passenger motor vehicles, commercial vehicles, buses and two-wheel vehicles. Also suitable for cooling circuit with filters.

Application

Shake well before use. Add contents to the cold cooling system. Start up the heater. Then drive the vehicle for at least 10 minutes. Contents (250 mL) is sufficient for 10 Liters (2.6 gal.) coolant.

Comment

 **WARNING:** Reproductive Harm - www.P65Warnings.ca.gov.