

Product information

Motorbike Speed Shooter

PI 33/26/08/2020



Description

A unique, state-of-the-art combination of acceleration-enhancing, cleaning, dispersing and material-protecting additives. Easy engine start, smoother running and better throttle response are the effects.

Properties

- good corrosion protection
- residue-free combustion
- promotes optimum combustion
- improves the acceleration
- removes deposits from entire fuel system
- very economical
- prevents carburetor icing
- increased performance

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb, klar / yellow, clear
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	<7 mm ² /s
Density at 68 °F	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>142 °F

Areas of application

Suitable for all 2- stroke and 4-stroke gasoline engines. Safe with catalytic converters.

Application

Contents (80 mL) is sufficient for 5–10 Liters (1.3 gal. to 2.6 gal.) gasoline. Add at every fill-up.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov



Available pack sizes

80 ml Can sheet metal	20140 USA (-EN-)
80 ml Can sheet metal	20346 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.