Product information

Motorbike 4T Shooter



Description

Removes deposits from the fuel system, valves, spark plugs and the combustion chamber while preventing new deposit formation. Improves engine performance and lowers emissions. Provides corrosion protection throughout and prevents carburetor icing.

Properties

- good corrosion protection
- environmentally friendly
- for carburetor and fuel-injection engines
- tested for the use with catalytic converters
- reduces residues
- optimizes engine performance
- normalizes fuel consumption and exhaust emissions values
- very economical
- increases operational reliability

Technical data

Base Additiv-Kombination in

Trägerflüssigkeit / additive mixture in liquid

carrier

Color / appearance hellgelb, klar / light

yellow, clear

Regulation on Flammable AII

Liquids Class (Germany)

Flash point >142 °F
Pour point -49 °F

Form flüssig / liquid
Odor charakteristisch /

characteristic

Viscosity at 104 °F $<7 \text{ mm}^2/\text{s}$ Density at 59 °F $0,765 \text{ g/cm}^3$

Areas of application

Suitable for all 4-stroke gasoline engines. Safe with catalytic converters.

Application

Contents (80 mL) is sufficient for 5–10 Liters (1.3 gal. to 2.6 gal.) gasoline. Add at every fill-up.

Comment

MARNING: Cancer- www.P65Warnings.ca.gov



Available pack sizes

80 ml Can sheet metal 20142

USA (-EN-)

80 ml Can sheet metal 20348

CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.