

# Product information

## Super Diesel Additive

PI 54/14/09/2020



### Description

A combination of additives to clean and maintain the diesel fuel system. Prevents corrosion, increases lubrication thus reduces fuel pump and injector wear. Increases Cetane value for improved engine performance, easier starting and lower emissions. Regular use keeps the fuel system in perfect working order.

### Properties

- keeps the fuel system clean
- for low-sulfur diesel fuels
- keeps injector nozzles clean
- tested for the use with catalytic converters
- prevents seizing and the injector needles from gumming up
- boosts the cetane number
- optimizes engine performance
- increases the lubricating effect
- excellent cleanliness
- prevents the build-up of deposits
- good corrosion protection
- guarantees low fuel consumption
- very wear resistant

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	145 °F
Pour point	- 97 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic

### Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

### Application

For best results and long-term effect add Super Diesel Additive every 2.000 km (1.200 miles). Contents (300 mL) is sufficient for 25–75 Liters (7 gal. to 20 gal.) fuel.



### Comment

 **WARNING:** Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### Available pack sizes

300 ml Can sheet metal	2002 USA (-EN-)
300 ml Can sheet metal	7702 CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**