

ATF Additive

Description

Keeps rubber and plastic seals in automatic transmissions soft and pliable. Leaks caused by hardened and brittle seals are prevented or eliminated. Cleans internal oil passages to allow proper oil flow while restoring the oils performance. Reduces noise and improves shift performance in automatic transmissions. Extends usable transmission life.

Properties

- regenerates seals
- prevents oil loss
- care and protection
- cleans and maintains
- stable to oxidation
- minimizes unwanted noise
- prevents expensive repairs
- increases service life
- very wear resistant
- prevents rapid aging of oil
- damps shifting operations

Technical data

Color / appearance	braun / brown
Viscosity at 104 °F	~ 166 mm ² /s DIN 51562
Viscosity at 212°F	~ 26 mm ² /s DIN 51562
Density	0,888 g/ml
Refractive index at 68 °F	~ 1,478
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

For all automatic transmissions that are filled with Dexron II and Dexron III based fluids.

Application

Mix ATF Additive into the gear oil using the dipstick. Contents (250 mL) is sufficient for 4–8 Liters (1.0 gal. to 2.1 gal.) ATF fluid.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov



Available pack sizes

250 ml Tube plastic

20040

USA AND CANADA (-EN-
F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.