



ADJUSTABLE BALL MOUNT WITH BALL PLATFORM

Assembly & Installation
Instructions

PART
NUMBER 33108

INSTALL
TIME 5
MINUTES

DEALER / INSTALLER

Provide a copy of these instructions to the end user of this product. These instructions provide important operating and safety information for proper usage of this product. Demonstrate the proper use of the product with the end user. Have the end user demonstrate that they understand the proper use of the product.

END USER ⚠ WARNING ⚠

Read and follow all instructions included in this manual. Ask your Dealer / Installer for assistance if you do not understand the proper use of the product. Never remove any decals from the product. Failure to follow these instructions can result in injury or death.

⚠ WARNING ⚠

DO NOT EXCEED Recommended towing limits. **SEE VEHICLE'S OWNER'S MANUAL.**

CONTENTS		33108 ADJUSTABLE BALL MOUNT WITH BALL PLATFORM	33111 REPLACEMENT PINS FOR ADJUSTABLE BALL MOUNT
ITEM NO.	DESCRIPTION	QTY	QTY
1	SHANK	1	-
2	PIN	2	2
3	HAIR PIN *	3	2
4	BALL PLATFORM	1	-
5	RUBBER BUMPER	1	-
6	HITCH PIN **	1	-

* ONLY 2 HAIR PINS SHOWN IN PHOTO

** HITCH PIN NOT SHOWN IN PHOTO



⚠ WARNING ⚠

USE ONLY SUPPLIED HARDWARE TO INSTALL THIS KIT.

Disclaimer:

The ratings of the adjustable ball mount kit and platform are intended to represent the capability of the product, and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

The adjustable ball mount kit consists of two separate parts referred to as the adjustable ball mount and the ball platform. Both the adjustable ball mount and the ball platform are rated to 6,000 lbs. Gross Vehicle Weight Rating (GVWR) / 600 lbs. tongue weight when using a hitch ball having a 1" shank and rated to a minimum 6,000 lbs. GVWR / 600 lbs. tongue weight. The hitch ball is not included. Use ONLY a hitch ball with a 1" shank.



WARNING: Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

1. Install the adjustable ball mount into the 2" receiver hitch of your vehicle and secure it with the included hitch pin and hair pin. Always secure the hitch pin with a hair pin unless a locking device is being used.
2. Install the hitch ball of your choice (with a 1" shank, and minimum 6,000lbs rating) into the ball platform. If you are not familiar with this process, and/or do not have the proper tools – you must have this ball installed by an experienced dealer capable of tightening and checking the torque of the hitch ball and nut. The hitch ball must be installed as per the manufacturer's specifications. Failure to do so could be a serious safety hazard to you and others.
3. Determine the height at which you need to install the ball platform on to the adjustable ball mount. Raise or lower the ball platform to the desired height and insert the supplied yellow pins through the holes that line up with the holes in the adjustable ball mount. Before the ball platform is set to the correct height and secured, insert the rubber dampener tightly into the channel-mount to eliminate noise. Secure the pins with the included hair pins.



WARNING: Use of any pin other than the pin supplied by Husky Towing could be a serious safety hazard and will void the warranty.

NOTE:

The supplied pins are specifically engineered for the adjustable ball mount. If replacement pins are needed, they must be replaced with original factory adjustable ball mount pins.



WARNING: Please ensure that the safety chains operate freely around the adjustable ball mount kit and do not become entangled in the Platform or Dual Flange Ball.

NOTES:

Prior to towing, check to make sure that the pins are secured into place with hair pins.
Never hook up trailer safety chains to the adjustable ball mount or ball platform.
The function of the pre-installed rubber bumper is to reduce rattles only.

RECOMMENDED PRODUCTS

2" Ball - 32914

2-5/16" Ball - 34919

Locking Pin Set - 33112

2-5/16" 6.5 Ton Pintle Ball Combo - 33114

Adjustable Step Platform - 33257

WARRANTY TERMS

5 Year Limited Warranty:

The warranty applies to products used for individual and private use. Commercial usage of the product limits the warranty to one year from date of purchase.

What is covered by the warranty?

This warranty covers defects in materials and workmanship to the original purchaser for five years from the date of purchase. If the product is used for commercial use the warranty period is limited to one year from date of purchase.

The warranty does not cover:

Service or labor charges associated with the removal or replacement or return of this product.

Product finish (paint, chrome, etc.).

Product neglect, abuse, misuse or products involved in accidents or acts of God.

Improper use of this product (overloading or improper installation).

Any alterations to this product.

Wear/ Tear items such as the Rubber Bumper (anti-rattle component).

Procedure for warranty:

1. Contact the manufacturer at phone: 877-544-4449.
2. The original sales receipt from original owner must be provided during the Warranty/RMA Process.

If the product is found to be defective, the product may be repaired or replaced at the discretion of the manufacturer, owner shall be responsible for all transportation cost associated with the return of any products.

The manufacturer shall not be liable for any incidental or consequential damages, whether arising out of breach of contract or claimed defect in, or non-performance of the products.

This warranty gives you specific legal rights, and you may also have other legal rights that vary from state to state.