



# LOCKING PIN SET FOR ADJUSTABLE BALL MOUNT KITS

Assembly & Installation Instructions

PART NUMBER	33112
INSTALL TIME	2 MINUTES

<b>DEALER / INSTALLER</b>	Provide a copy of these instructions to the end user of this product. These instructions provide important operating and safety information for proper usage of this product. Demonstrate the proper use of the product with the end user. Have the end user demonstrate that they understand the proper use of the product.
---------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>END USER WARNING</b>	Read and follow all instructions included in this manual. Ask your Dealer/Installer for assistance if you do not understand the proper use of the product. Never remove any decals from the product. Failure to follow these instructions can result in injury or death.
-------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>WARNING</b>	<b>DO NOT EXCEED</b> Recommended towing limits. <b>SEE VEHICLE'S OWNER'S MANUAL.</b>
----------------	--------------------------------------------------------------------------------------

CONTENTS		33112 ADJUSTABLE BALL MOUNT LOCKING PIN KIT
ITEM NO.	DESCRIPTION	QTY
1	SHORT LOCKING PIN	1
2	LONG LOCKING PIN	1
3	LOCK FOR SHORT PIN	1
4	LOCK FOR LONG PIN	1
5	KEY FOR SHORT PIN	2
6	KEY FOR LONG PIN	2



Pin Capacity: 20,000 lbs. Maximum.

<b>WARNING</b>	<b>USE ONLY SUPPLIED HARDWARE TO INSTALL THIS KIT.</b>
----------------	--------------------------------------------------------

## Mounting:

These pins can only be used with the adjustable ball mount kit. If you are not yet familiar with how your adjustable ball mount system works, it is recommended that you familiarize yourself with operating instructions prior to towing and using these pins. Failure to do so can result in possible accidents and/or injuries.

## Towing Applications:

Trailers and equipment designed for over-the-road towing within the stated capacities.

## System Capacities:

Be sure to double check the capacity of your entire towing hitch system. Use the trailer coupler capacity, or the capacity listed above, whichever is lower. If trailer coupler capacity is unknown, do not exceed the maximum towing capacity which is stamped on either your trailer balls or accessories.

## Operation Instructions:

Before operating, inspect for proper operation, worn, damaged or missing parts and secure mounting. Correct as required before use. Be sure to fully inspect the vehicle's receiver hitch, the adjustable ball mount and its respective hardware. If you doubt the condition of any of the parts or accessories or your vehicle's hitch system – **do not** tow and contact your sales dealer for replacement parts.



Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less. See your Vehicle Owners Manual to determine Vehicle Tow Rating.

## Installation:

1. Replace your current receiver hitch pin with the shorter locking bent pin included with this kit. To remove and re-install the lock, simply insert the included key and turn to lock and unlock the set. Your old receiver pin will no longer be used, as your Husky® Platform hitch is now secured to the tow vehicle's hitch.
2. To secure your Husky® accessory to the platform, install the longer straight locking pin into the bottom hole of the accessory you wish to secure. When correctly installed, the upper hole of the accessory will be secured with the standard yellow pin which was included with your Husky® kit. The bottom hole will now be secured with your locking pin.

### NOTE:

The supplied pins are specifically engineered for the adjustable ball mount kit. If replacement pins are needed, they must be replaced with original factory adjustable ball mount kit pins.

Prior to towing, check to make sure that the pins are secured into place.



**WARNING:** These locking pins do not promise or guarantee the security of your vehicles, trailers, hitches or contents. Husky® and the manufacturer cannot be held liable for any damages or losses as a result of theft or vandalism of any property. **Always double-check your towing apparatus and hardware before resuming towing to be sure that they are in good working condition and installed correctly.**



**WARNING:** Use of any pin other than the pin supplied by Husky Towing could be a serious safety hazard and will void the warranty.



**WARNING:** Please ensure that the safety chains operate freely around the adjustable ball mount kit and do not become entangled in the Platform or Dual Flange Ball.

# **WARRANTY TERMS**

## **5 Year Limited Warranty:**

The warranty applies to products used for individual and private use. Commercial usage of the product limits the warranty to one year from date of purchase.

## **What is covered by the warranty?**

This warranty covers defects in materials and workmanship to the original purchaser for five years from the date of purchase. If the product is used for commercial use the warranty period is limited to one year from date of purchase.

## **The warranty does not cover:**

Service or labor charges associated with the removal or replacement or return of this product.

Product finish (paint, chrome, etc.).

Product neglect, abuse, misuse or products involved in accidents or acts of God.

Improper use of this product (overloading or improper installation).

Any alterations to this product.

Wear/ Tear items such as the Rubber Bumper (anti-rattle component).

## **Procedure for warranty:**

1. Contact the manufacturer at phone: 877-544-4449.
2. The original sales receipt from original owner must be provided during the Warranty/RMA Process.

If the product is found to be defective, the product may be repaired or replaced at the discretion of the manufacturer, owner shall be responsible for all transportation cost associated with the return of any products.

The manufacturer shall not be liable for any incidental or consequential damages, whether arising out of breach of contract or claimed defect in, or non-performance of the products.

This warranty gives you specific legal rights, and you may also have other legal rights that vary from state to state.