

CCI® CENTER REPLACEMENT IWCC5502









READ INSTRUCTIONS CAREFULLY BEFORE STARTING INSTALLATION. PICTURES ARE FOR DEMOSTRATION PURPOSES ONLY.

INSTALLATION PROCEDURE

- 1. Open the box and thoroughly inspect all pieces of your CCI® Center Cap Replacements for any shipping damage or manufacturer defects before installing product. Verify your CCI® Center Cap Replacement matches the physical design of the OEM center cap. If damaged, defects are found or does not match the OEM center cap. Place product back into its box with all its original packaging and contact your distributor for credit or replacement. Any product installed may void product's warranty for shipment damage or manufacturer's defects.
- 2. Your CCI® Center Cap Replacement is similar to the OEM center cap design. This center cap is designed to fit multiple wheels. Some wheels may need the retention ring and others may not. Look at the back of your CCI® Center Cap Replacement to see the retention ring. If the center cap is to tight, you may remove the ring before installing, see Fig. 1.
- 3. Wipe clean all areas that your CCI® Center Cap Replacement will be installed. Remove any dust or dirt that may otherwise hinder installation.
- 4. Line up your CCI® Center Cap Replacement to the OEM wheel and push into place with a straight on forward motion until all tabs have snapped in.



- 5. Repeat steps 2-4 for all remaining pieces.
- 6. Wipe down your installed CCI® Center Cap Replacements with a soft dry cloth to a showroom shine.

PRODUCT CARE

- Regular vehicle cleaning of dirt, grime or salt twice a month, year round.
- Appling a high-quality wax to help protect and maintain the finish of the product is recommended.
- Use ONLY Non-Abrasive automotive wax. Use of any soap, polish or wax that contains an abrasive is
 detrimental and can scratch the finish leading to corrosion.
- Failure to keep your product clean may result in pitting and or peeling.

DISCLAIMER:

CCI® guarantees our chrome products against material and workmanship defects for as long as you own your vehicle. Any defects resulting from faulty materials, finish or workmanship will be warranted by CCI® and repaired, replaced, or credited at our discretion. CCI® assumes no extra labor costs. Damages caused by freight carriers, improper installation, misuse, collision, normal wear and tear or neglect will not be warranted by CCI®.

Page 1 of 1 BAO 05/30/16