




WEB LINK: http://lodoffroad.com/assets/pdfs/JFT2000 JT Rear Bumper Frame Tie In Brackets.pdf

\*VERIFY YOU HAVE ALL THE COMPONENTS BEFORE STARTING THE INSTALLATION. REFER TO THE ENGINEERING DRAWINGS AT THE END OF THIS DOCUMENT FOR A COMPLETE PARTS LIST\*





\*\*\*Be sure to read through the entire instructions before starting your installation!\*\*\*

Refer to the Engineering drawing included with this document for the correct hardware required at each step of the installation.

Install the Frame Tie In Brackets on top of the frame rail and behind the frame rail face plate as shown.




Use the 1/2" Hex Bolts, Nuts and Washers that come with your LOD Rear Bumper to attach the Frame Tie In Brackets.

These Hex Bolts, Nuts and Washers are included with your Rear Bumper Bolt Kit.



Install Backing Washer/Spacer as shown between your Frame Tie In Bracket and the Bumper Frame Mount after you bumper is installed.





Install the Face Plate or D-Ring Mount on your bumper and tighten securely.




## \*\*Maintenance\*\*

- Periodically check and re-tighten all fasteners.
- Periodically check your product for scratches or dings which can happen over time or after heavy use or highway driving. It is important to address these areas as soon as possible to prevent flaking and corrosion or rust from spreading. We recommend using Rustoleum<sup>©</sup> brand Black Semi-Gloss Protective Enamel (oil based). Remove loose powder coating, sand the area and clean using alcohol. Apply using a foam brush by dabbing to match the powder coat texture.











## JT Jeep DESTROYER SERIES


JEEP JT REAR BUMPER FRAME TIE IN BRACKETS SHIPPING SHEET


| Packaged by: |
|--------------|
|              |

On:










JT REAR FRAME TIE IN WELDMENT - PS
4JRB2000-02
(x1)



BACKING WASHER / SPACER
2JRS0754-19
(x2)