



## MBRP Muffler Installation Instructions

3010311

'98-'03

SRX 600 & 700

**Note:** Local regulations may limit or prohibit modification to your snowmobile's emissions system and/or the sound levels that it generates. It is your responsibility to be aware of restrictions that may apply to your intended use of this product.

1. Remove the springs fastening the stock muffler to the frame and the exhaust pipe. (Set these springs safely aside so that they can be reused.)
2. Remove the stock muffler.
3. Install the MBRP Muffler to fit in the original hole in the belly pan.
4. Remove the rectangular rubber piece from the stock exhaust where the pipe chambers rested.
5. Test fit the MBRP muffler and the stock pipes. Your pipes should now be resting on the belly pan.
6. Mark the area where the pipes are resting and drill two 5/8" holes to mount the rubber piece.
7. You are now ready to install the unit for the final fit using all of the stock springs and mounting locations.
8. After the final installation, place the heat retardant tape on the black portion of the top of the belly pan to deter any discoloration.

**NOTE:** To avoid exhaust leaks use a high heat silicone to seal all connections between the expansion chambers and the muffler. Monitor the exhaust for leaks during the first 200 miles after your installation and re-apply silicone where necessary. We suggest having your local snowmobile mechanic or performance shop install this product.

**CAUTION:** **DO NOT** touch the muffler while the snowmobile is running or shortly after it has run, as it may result in personal injury.

MBRP Ltd. warranty applies for a two (2) year period from the date of purchase to defects in product material and workmanship and is to the original purchaser on record and for the original vehicle for which it was designed and installed. This warranty is limited, at MBRP Ltd.'s sole determination, to the repair or replacement of defective product only and does not include the cost of removal or re-installation, damage by accident, abuse, misuse or misapplication or any consequential damages however they may arise. Determination of warranty coverage shall be at the discretion of an authorized MBRP Ltd. quality engineer.