


AUXILIARY HEATER AH454/12 VOLT

Heater • Mounting Brackets • Instruction Sheet • Installation Kit

INSTALLATION KIT INCLUDES:







Clamps










Grommets

(1) Rocker

Switch Screws


(1) Switch Panel

INSTALLATION DIAGRAM:



INSTALLATION INSTRUCTIONS:

- 1. This versatile heater may be mounted either horizontally or vertically. Typical locations include floor, wall or under dash.
- 2. Route the heater hose to the engine compartment, using grommets through the fire wall, cut the existing hose, add and clamp the Y splicer then run the new hose and clamp to the heater. Avoid any sharp bends which may kink the hose and restrict proper flow. Run Y splicer with the coolant flow. (See splicer diagram.)
- 3. Mount the switch panel in a convenient under dash location. Route power supply wire from fuse block to switch, including the inline 7.5A amp fuse. Connect the red and orange wires from the heater to the switch, extending them where necessary. And finally, ground the heater case to the chassis of the vehicle. (See the connection diagram below.)



LIMITED WARRANTY

Northern Factory Sales warranties its Heaters to be free from all defects in manufacturing and workmanship for one year from the date of installation.

Any Heater claimed defective under this limited warranty should be forwarded to Northern Factory Sales, transportation charges prepaid, for inspection and warranty determination.

Northern Factory Sales will not be responsible for heaters damaged from misuse or neglect. Any expense associated with a warranty replacement, including but not limited to installation and transportation charges, are not covered under this warranty. This warranty provides for product replacement only. Any attempt at local repairs automatically voids this limited warranty.