



ORACLE LIGHTING

2016-2021 TESLA MODEL X
ORACLE PART #1467-332
INSTALLATION GUIDE

TOOLS NEEDED:

SCREWDRIVER, DRILL,
DRILL BITS, MULTIT-TOOL,
SEALANT, MASKING TAPE

STEP: 1

WATCH THE VIDEO
SCAN QR OR VISIT:



WWW.VIMEO.COM/571765583



UNSCREW THE BOTTOM
SUPPORT BRACKET

2



WE'RE USING A MULTI TOOL
TO CUT OPEN IN THE LENS

3



USE A FLATHEAD
TO SEPERATE THE LENS
IF NEEDED

4



USE A 9/16 BIT TO DRILL
A HOLE FOR WIRING

5



REMOVE THE TAPE BACKING
ON THE BOARD

6



FIRMLY PRESS THE STRIP ON
THE EDGE OF THE LOWER PART
OF THE INNER HOUSING

7



DRILL A HOLE IN THE
BACK OF THE HEADLIGHT

8



RUN THE WIRING THROUGH THE HOLE

9



PART#
2001-504

USE ORACLE SEALANT
TO SEAL THE HEADLIGHT

10



SET FOGLIGHT INTO OVEN
225°F FOR 12 MINUTES

11



USE A FLATHEAD SCREWDRIVER
TO SEPERATE LENS FROM HOUSING

12



USE PHILIPS SCREWDRIVER
TO REMOVE INNER HOUSING

13



UNPLUG THE BOARDS
FROM THE INNER HOUSING

14



UNCLIP THE FRONT LENS

15



DRILL A 9/16TH HOLE
IN THE TOP CORNER

16



REMOVE TAPE BACKING
AND SECURE ON OUTER WALL

17



RESET LIGHT INTO HOUSING
MAKE SURE IT CLICKS BACK IN

18



DRILL A HOLE TO RUN
THE WIRING THROUGH

19



USE ORACLE SEALANT TO
RESECURE LENS TO HOUSING

20

ORACLE
LIGHTING

www.oraclelights.com

© 2020 ORACLE LIGHTING

4401 Division St.
Metairie, LA 70002

FOR ADDITIONAL TECHNICAL SUPPORT PLEASE CALL US 1(800)407-5776