



JEEP 2018-UP JL Rear LED Tail Lights

Thank you for choosing Rough Country for all your vehicle needs.

Please read instructions before beginning installation. Check the kit hardware against the kit contents shown below. Be sure you have all needed parts and know where they go.

If question exist, please call us @1-800-222-7023. We will be happy to answer any questions concerning this product.

Check all fasteners for proper torque. Check to ensure for adequate clearance between all components.

Periodically check all hardware for tightness.

KIT CONTENTS:

- Driver Side Tail Light x1
- Pass Side Tail Light x1

TOOLS NEEDED:

- Flat Pry Tool
- Phillips Bit Driver
- 10mm Wrench or Socket





Torque Specs:

Size	Grade 5	Grade 8	Size	Class 8.8	Class 10.9
5/16"	15 ft/lbs	20ft/lbs	6MM	5ft/lbs	9ft/lbs
3/8"	30 ft/lbs	35ft/lbs	8MM	18ft/lbs	23ft/lbs
7/16"	45 ft/lbs	60ft/lbs	10MM	32ft/lbs	45ft/lbs
1/2"	65 ft/lbs	90ft/lbs	12MM	55ft/lbs	75ft/lbs
9/16"	95 ft/lbs	130ft/lbs	14MM	85ft/lbs	120ft/lbs
5/8"	135ft/lbs	175ft/lbs	16MM	130ft/lbs	165ft/lbs
3/4"	185ft/lbs	280ft/lbs	18MM	170ft/lbs	240ft/lbs



INSTALLATION INSTRUCTIONS



1. Locate the interior bolt cover on the inside of the vehicle. Using a Flat pry tool remove the cover. **See Photo 1.**
2. Loosen the tail light bolt using a 10mm socket. Retain the bolt for reuse. **See Photo 2.**




3. Remove the bolt and the tail light from the vehicle. **See Photo 3.**
4. Release the center lock tab. Then disconnect the plug. **See Photo 4.**





5. Remove the mounting bracket from the tail light. Using a Phillips bit driver remove the (3) screws from the mount. Then release the clip and remove the bracket from the tail light. **See Photo 5.**
6. Place the mount onto the new tail light, seating the clip into the base of the light. Secure the mount using the (3) retained screws. **See Photo 6.**



7. Connect the wiring harness from the new tail light to the vehicle harness and lock the tab in place. **See Photo 7.**
8. Install the tail light into the vehicle. **See Photo 8.**



9. Install the tail light bolt into the bracket. Snug using a 10mm socket. Do not over tighten. **See Photo 9.**
10. Install the interior bolt cover. **See Photo 10.**
11. Repeat steps 1-10 on the opposite side of the vehicle.



12. After installation of the tail lights check that all functions of the tail light are to be in working order.

By purchasing any item sold by Rough Country, LLC, the buyer expressly warrants that he/she is in compliance with all applicable, State, and Local laws and regulations regarding the purchase, ownership, and use of the item. It shall be the buyers responsibility to comply with all Federal, State and Local laws governing the sales of any items listed, illustrated or sold. The buyer expressly agrees to indemnify and hold harmless Rough Country, LLC for all claims resulting directly or indirectly from the purchase, ownership, or use of the items.

