Printing date 01/02/2018 Revised On 01/02/2018

1 Identification of the substance and manufacturer

CLEAR Trade name:

0000100031 **Product code:**

Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue

Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924 Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation. Skin Irrit. 2

H319 Causes serious eye irritation. Eye Irrit. 2A STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerou	Dangerous components:						
67-64-1	Acetone	30.14%					
74-98-6	propane	15.75%					
110-19-0	Isobutyl Acetate	13.05%					
	butyl acetate	9.94%					
111-76-2	Glycol Ether EB	9.94%					
106-97-8	n-butane	9.25%					

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Remove contaminated clothing. Wash exposed area with soap and water.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures. Special hazards:

(Contd. on page 2)

Printing date 01/02/2018 Revised On 01/02/2018

Trade name: CLEAR

Protective equipment for firefighters:

A respiratory protective device may be necessary.

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency

Wear protective equipment. Keep unprotected persons away

procedures:

Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing

conditions. Store locked up.

8 Exposure controls/personal protection

Components wit	limit values that require monitoring at the workplace:
C7 C4 4 Asstsus	<u> </u>

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm TLV (USA) Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm

BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm TLV (USA) refer to Appendix F inTLVs&BEIs book; D, EX

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm REL (USA) Long-term value: 700 mg/m³, 150 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

123-86-4 butyl acetate

PEL (USA) Long-term value: 710 mg/m³, 150 ppm REL (USA) Long-term value: 950 mg/m³, 200 ppm TLV (USA) Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

111-76-2 Glycol Ether EB

PEL (USA) Long-term value: 240 mg/m³, 50 ppm Skin

REL (USA) Long-term value: 24 mg/m3, 5 ppm

Skin

TLV (USA) Long-term value: 97 mg/m³, 20 ppm BEI

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX)

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

111-76-2 Glycol Ether EB

BEI (USA) 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

(Contd. on page 3)

Printing date 01/02/2018 Revised On 01/02/2018

Trade name: CLEAR

Eye protection: (Contd. of page 2)

Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47.2 °F) **Boiling point:** Flash point: -19 °C (-2.2 °F) Extremely flammable. Flammability (solid, gas): **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density
Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Not determined.
Not determined.
Not determined.
Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

	_							
LD/LC50 values that are relevant for classification:								
110-19-0 Isobutyl Acetate								
Oral	LD50	4,763 mg/kg (rbt)						
123-86-4 k	123-86-4 butyl acetate							
Oral	LD50	14,000 mg/kg (rat)						
Inhalative	LC50/4 h	>21 mg/l (rat)						
111-76-2 Glycol Ether EB								
Oral	LD50	1,480 mg/kg (rat)						
Dermal	LD50	400 mg/kg (rab)						
106-97-8 r	106-97-8 n-butane							
Inhalative	LC50/4 h	658 mg/l (rat)						

Inhalative LC50/4 h 658 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:

Mobility in soil:

Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

 UN-Number
 UN1950

 DOT
 N/A

 UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable

ADR 1950 Aerosols

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet

Printing date 01/02/2018 Revised On 01/02/2018

Trade name: CLEAR

Transport hazard class(es):

Marine pollutant:

Class 2.1 No Special precautions for user:

Warning: Gases EMS Number: F-D,S-Ŭ

Packaging Group:

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

111-76-2 Glycol Ether EB

Toxic Substances Control Act

(TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety Comission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients in this product are listed.

CANADIAN ENVIRONMENTAL WHMIS Symbols for Canada:

PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A - Compressed gas

D2B - Toxic material causing other toxic effects



EPA:		
67-64-1	Acetone	I
	Isobutyl Acetate	D
111-76-2	Glycol Ether EB	NL

16 Other information

Contact: Regulatory Affairs Date of preparation / last revision 01/02/2018 / -