Printing date 01/05/2018 Revised On 01/05/2018

1 Identification of the substance and manufacturer

OMAHA ORANGE Trade name: 0006201450 **Product code:**

Manufacturer/Supplier: Seymour of Sycamore 917 Crosby Avenue

Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924 Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation. Eye Irrit. 2A STOT SE 3 H336 May cause drowsiness or dizziness

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard-determining components of

labeling:

Acetone butyl acetate

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautionary statements Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place.

Store locked up Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

Physical dangers:

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also

damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the

contents may be harmful or fatal.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Chombal Decomplian		The production a mixture of the eductations hered below with horning additioner		
	s components:			
67-64-1	Acetone		19.71%	
	propane		15.71%	
	barium sulfate		9.42%	
106-97-8			9.23%	
	Isobutyl Acetate		7.06%	
	Glycol Ether EP		7.06%	
	butyl acetate		3.59%	
	PM acetate		2.64%	
107-87-9	Methyl Propyl Ketone		1.42%	

4 First-aid measures

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor.

After swallowing: Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/05/2018 Revised On 01/05/2018

Trade name: OMAHA ORANGE

Information for doctor:

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing media **Extinguishing agents:** Special hazards:

Protective equipment for

firefighters:

Additional information

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary. Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol. Do not allow product to reach sewage systems or ground water.

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Environmental precautions: Methods and material for

containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Fire/explosion protection:

Use only in well ventilated areas.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from

electrostatic discharges.

Conditions for safe storage:

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that

require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or

other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

67-64-1 Acetone PEL

Long-term value: 2400 mg/m³, 1000 ppm **REL** Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

74-98-6 propane

TLV

REL

TLV

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

refer to Appendix F inTLVs&BEIs book; D, EX

7727-43-7 barium sulfate

Long-term value: 15* 5** mg/m³ *total dust **respirable fraction PEL

Long-term value: 10* 5** mg/m³ *total dust **respirable fraction

TLV

Long-term value: 5* mg/m³ *inhalable fraction; E

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppm

Short-term value: 2370 mg/m³, 1000 ppm

(EX)

110-19-0 Isobutyl Acetate

Long-term value: 700 mg/m³, 150 ppm PEL

REL Long-term value: 700 mg/m³, 150 ppm TLV

Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm

123-86-4 butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Long-term value: 950 mg/m³, 200 ppm

Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm TLV

108-65-6 PM acetate

WEEL Long-term value: 50 ppm

107-87-9 Methyl Propyl Ketone

PEL Long-term value: 700 mg/m³, 200 ppm

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/05/2018 Revised On 01/05/2018

Trade name: OMAHA ORANGE

REL Long-term value: 530 mg/m³, 150 ppm TLV

Short-term value: 529 mg/m³, 150 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Exposure controls

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

General Information:

Appearance: Aerosol Odor: Aromatic Odor threshold: Not determined. pH-value: Melting point/Melting range Not determined Undetermined. **Boiling point:** -44 °C (-47.2 °F)

-19 °C (-2.2 °F) Flash point: **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % **Upper Explosion Limit:** 10.9 Vol %

Vapor pressure: 2750 hPa Vapor Pressure: 40 PSI, 2750 hPa

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. Dynamić: Not determined. Kinematic: Not determined.

Water: 0.0 %

10 Stability and reactivity

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid No further relevant information available. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:						
106-97-8 n-butane						
Inhalative LC50/4 h 658 mg/l (rat)						
110-19-0 Isobutyl Acetate						
Oral	LD50	4,763 mg/kg (rbt)				
123-86-4 butyl acetate						
Oral	LD50	14,000 mg/kg (rat)				
Inhalative	LC50/4 h	>21 mg/l (rat)				
108-65-6 PM acetate						

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Skin effects: No irritant effect. Eye effects: Irritating effect.

(Contd. on page 4)

(Contd. of page 3)

Printing date 01/05/2018 Revised On 01/05/2018

Trade name: OMAHA ORANGE

Sensitization:

No sensitizing effects known.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents. Other information:

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. Not applicable. vPvB:

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT N/A

UN proper shipping name: DOT

Transport hazard class(es):

2.1 Class Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number:

Stowage Code

F-D,S-U
SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living

quarters.

Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation

as for the appropriate subdivision of class 2.

Consumer Commodity ORM-D

Packaging Group:

15 Regulatory information

Toxic Substances Control Act (TSCA):

Consumer Product Safety

All hazardous ingredients for this product are found on the inventory list of substances.

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone

100-41-4 ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-10-1 methyl isobutyl ketone

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:		
67-64-1	Acetone	I
7727-43-7	barium sulfate	D, CBD(inh), NL(oral)
110-19-0	Isobutyl Acetate	D

USDA (United States Department of

Agriculture):

Category 21: This product was manufactured to conform to the USDA Food Safety and Inspection Service performance standards. These standards include, but are not limited to, the ability of this product to be safe for use in official meat and poultry establishments, and to perform well under a daily regimen of thorough cleaning, cyclical temperature change, and wet conditions. This product may be used where there is a possibility of incidental food contact. The product is classified and labeled according to the Globally Harmonized System (GHS).

GHS label elements

Extremely flammable aerosol. Hazard statements

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet

Printing date 01/05/2018 Revised On 01/05/2018

Trade name: OMAHA ORANGE

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F

Dispose of contents/container in accordance with local/regional/national/international

regulations.
A Chemical Safety Assessment has not been carried out. **Chemical safety assessment:**

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

Regulatory Affairs 01/05/2018 / -

Date of preparation / last revision Abbreviations and acronyms:

01/05/2018 /
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Aerosol 1: Aerosols – Category 1
Press. Gas: Gases under pressure – Liquefied gas
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (repeated exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2