


Extreme Grille Guard




PARTS LIST:			
Qty	Part Description	Qty	Part Description
4	M12*35 Hex Head Bolts	6	M12 Lock Washer
2	M12*60 Hex Head Bolts	12	Flat Washer(12.5mm*30.1mm*3.1mm)
6	M12 Hex Nuts		

INSTALLATION PROCEDURE:

Step 1: Raise the Hood. Remove the two nuts on the side of the frame behind the frame cap (2500, 3500). Remove the two or three nuts on the back of the frame cap (1500). Insert upper grille guard support bracket and align to the two bolts, replace nuts and tighten. (Hint: the bracket should be below the hood 3/8" when the hood is closed).

Step 2: Remove the lower bumper bolt located on the bottom outside corner of frame cap. (Note: DO NOT REMOVE FACTORY BUMPER - Bumper is not shown in photos for illustration only!). Install lower support bracket behind to this bolt hole using 12mm X 60mm bolt supplied. Attach lower strap of Grille Guard to this bracket. Tighten bolt.



PRODUCT CARE

- Periodically check the product to ensure all fasteners are tight and components are intact.
- Regular waxing is recommended to protect the finish of the product.
- Use ONLY Non-Abrasive automotive wax. Use of any soap, polish or wax that contains an abrasive is detrimental and can scratch the finish leading to corrosion.
- Aluminum polish may be used to polish small scratches and scuffs for Stainless Steel finish.
- Mild soap may be used to clean the product for both Stainless Steel and Black finish.

FAQ's

1. Hardware's are not of correct size.

In GMC / Chevrolet truck model 2006 & up, customer needs to reuse the factory body bolts to install the bracket. If your vehicle is not GMC / Chevrolet 2006 & up, ensure that holes are not partially covered with any plastic grommet or rust? If it is, remove the plastic grommet & rust from the thread holes & re-try the installation.

2. Mounting Bracket are not getting Installed properly.

In some cases Illustration images shown in Installation manual may not be the exactly same as per actual vehicle images ,also if Driver / Passenger side mounting brackets are very identical in the design, suggest referring Parts Identification guide to avoid fitment issue.

3. Products are thumping / rattling after installation.

Ensure that all required mounting brackets / hardware's are installed & tighten correctly. Suggest using white lithium / regular grease between the metal to metal contact surfaces.

4. Side Bar is not aligning with vehicle / Step Pads are not aligning with vehicle doors. Side bar may be interchanged or mounting brackets are not installed at the correct position in the vehicle. Refer Parts identification guide.

5. Missing / Excess Hardware.


Recheck hardware count as per the part list.

6. Product not installing properly.

Ensure make model year, cab length and bed size of your vehicle is listed in the application. All installation steps are followed correctly.

Check out these other TrailFX Products!!

www.FX-Products.com



Keystone Automotive Operations Inc. (KAO) warrants this product to be free of defects in material and workmanship at the time of purchase by the original retail consumer. KAO disclaims any other warranties, express or implied, including the warranty of fitness for a particular purpose or an intended use. If the product is found to be defective, KAO may replace or repair the product at our option, when the product is returned prepaid, with proof of purchase. Alteration to, improper installation, or misuse of this product voids the warranty. KAO's liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for any incidental or consequential loss or damage.