

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations
Issue date: 4/5/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : VP RACING FOAM FILTER OIL (2917)
Product code : 10-502395
Vaporizer : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Intended for general public
Use of the substance/mixture : Lubricant
Restrictions on use : None known

1.4. Supplier's details

Spray Products Corporation
P.O. Box 954
Conshohocken, Pennsylvania 19428
USA
T (610) 277-1010 - F (610) 277-4390
sds@sprayproducts.com

1.5. Emergency phone number

Emergency number : CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol 1	H222;H229	Extremely flammable aerosol. Pressurized container; may burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: H222 - Extremely flammable aerosol
H229 - Pressurized container; may burst if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (treat symptomatically).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	wt%	GHS US classification
Heptane, branched, cyclic and linear	CAS-No.: 426260-76-6	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6	15 – 25	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
butane (Propellant gas (Aerosol))	CAS-No.: 106-97-8	10 – 15	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
POLYBUTENE	CAS-No.: 9003-29-6	10 – 15	Asp. Tox. 1, H304
distillates (petroleum), hydrotreated heavy naphthenic	CAS-No.: 64742-52-5	5 – 10	Asp. Tox. 1, H304
Residual oils (petroleum) solvent dewaxed IP 346 < 3%	CAS-No.: 64742-62-7	5 – 10	Asp. Tox. 1, H304

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Name	Product identifier	wt%	GHS US classification
heptane; n-heptane	CAS-No.: 142-82-5	< 2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401

The product is an aerosol. The components' disclosure has been adjusted to no longer include the propellant.
Full text of hazard classes and H-statements : see section 16

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No special technical protective measures are necessary.

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

For non-emergency personnel

Protective equipment : Not required.
Emergency procedures : Not required.

For emergency responders

Protective equipment : Not required.
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Mechanically recover the product. Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes.
Hygiene measures : Always wash hands after handling the product.
Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Not specifically applicable.
Storage conditions : Store at room temperature.
Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)	
Regulatory Standard No. 15 (NR-15): Unhealthy Activities and Operations	
Local name	Propanona (vide acetona)
Remark	-
Regulatory Reference	NR 15 (2022)
n-Butano (106-97-8)	
Regulatory Standard No. 15 (NR-15): Unhealthy Activities and Operations	
Local name	n-Butano
Remark	Medium
Regulatory Reference	NR 15 (2022)

8.2. Appropriate engineering controls

Appropriate engineering controls : Not required for normal conditions of use.
Environmental exposure controls : Avoid release to the environment.

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Not required.

Hand protection:
Not required
Eye protection:
Not required
Skin and body protection:
Not required
Respiratory protection:
No respiratory protection needed under normal use conditions

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol
Colour	: Colourless
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 mm ² /s @40°C
Explosive limits	: No data available
Explosive properties	: Pressurised container: May burst if heated.
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Not to be expected)
Acute toxicity (dermal) : Not classified (Not to be expected)
Acute toxicity (inhalation) : Not classified (Not to be expected)

propane (74-98-6)

LC50 Inhalation - Rat [ppm]	38890 ppm
-----------------------------	-----------

butane (106-97-8)

LC50 Inhalation - Rat [ppm]	276798.8 ppm
-----------------------------	--------------

Heptane, branched, cyclic and linear (426260-76-6)

LD50 oral rat	> 5840 mg/kg (By analogy to similar materials)
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 23.3 mg/l/4h (OECD TG 403)

heptane; n-heptane (142-82-5)

LD50 oral rat	> 5000 mg/kg bodyweight (OECD TG 401)
LD50 oral	5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD TG 402)
LD50 dermal	3000 mg/kg
LC50 Inhalation - Rat (Vapours)	25132 ppmv

POLYBUTENE (9003-29-6)

LD50 oral rat	> 2000 mg/kg bodyweight (OECD TG 401)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD TG 402)
LD50 dermal rabbit	> 10250 mg/kg
LC50 Inhalation - Rat	> 19.171 mg/l air (EPA OPPTS 870.1300)
LC50 Inhalation - Rat (Vapours)	> 0.85 mg/l

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LD50 oral rat	> 5000 mg/kg
LD50 oral	15000 mg/kg
LD50 dermal	5000 mg/kg

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Residual oils (petroleum) solvent dewaxed IP 346 < 3% (64742-62-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID

Skin corrosion/irritation : Causes skin irritation.

Heptane, branched, cyclic and linear (426260-76-6)	
Read-across, rabbit	Causes skin irritation (OECD 404 method)

heptane; n-heptane (142-82-5)	
Read-across, rabbit	Causes skin irritation (OECD 404 method)

POLYBUTENE (9003-29-6)	
Result, rabbit	Not irritating to skin (OECD 404 method)

Serious eye damage/irritation : Not classified (Not to be expected)

Heptane, branched, cyclic and linear (426260-76-6)	
Read-across, rabbit	Not irritating to eyes EPA OPPTS 870.2400

heptane; n-heptane (142-82-5)	
Read-across, rabbit	Not irritating to eyes (OECD 405 method)

POLYBUTENE (9003-29-6)	
Result, rabbit	Not irritating to eyes (OECD 405 method)

Respiratory or skin sensitisation : Not classified (Not to be expected)

Heptane, branched, cyclic and linear (426260-76-6)	
Read-across, Guinea pig	Not expected to be a skin sensitizer (OECD 406 method)

heptane; n-heptane (142-82-5)	
Read-across, Guinea pig	Not expected to be a skin sensitizer (OECD 406 method)

POLYBUTENE (9003-29-6)	
Result, mouse	May cause an allergic skin reaction (OECD 429 method)

Germ cell mutagenicity : Not classified (Not to be expected)

Heptane, branched, cyclic and linear (426260-76-6)	
Read-across, In vitro	Classification criteria are not met (OECD 471 method), (OECD 473 method), (OECD 476 method)
Read-across, In vivo	Classification criteria are not met (OECD 478 method)

heptane; n-heptane (142-82-5)	
Result, In vitro	Classification criteria are not met (OECD 471 method), (OECD 473 method)
Result, In vivo	Classification criteria are not met (OECD 478 method)

POLYBUTENE (9003-29-6)	
Result, In vitro	Classification criteria are not met (OECD 471 method), (OECD 487 method), (OECD 490 method)

Carcinogenicity : Not classified (Not to be expected)

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Reproductive toxicity : Not classified (Not to be expected)

Heptane, branched, cyclic and linear (426260-76-6)	
Read-across, oral, rat (OECD 414 method)	No significant developmental effects observed.
Read-across, Inhalation, rat Weight of evidence	No significant reproductive effects observed.
POLYBUTENE (9003-29-6)	
Result, oral, rat (OECD 422 method)	No reproductive or developmental effects observed.

STOT-single exposure : May cause drowsiness or dizziness.

Heptane, branched, cyclic and linear (426260-76-6)	
STOT-single exposure	May cause drowsiness or dizziness.
heptane; n-heptane (142-82-5)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Not to be expected)

Heptane, branched, cyclic and linear (426260-76-6)	
LOAEC (inhalation, rat, vapour, 90 days)	16.6 mg/l air
NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air
heptane; n-heptane (142-82-5)	
LOAEC (inhalation, rat, vapour, 90 days)	16.6 mg/l air
NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air
POLYBUTENE (9003-29-6)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight
NOAEC (inhalation, rat, vapour, 90 days)	1 mg/l air (OECD TG 422)
distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight (OECD TG 408)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air (OECD TG 412)
Residual oils (petroleum) solvent dewaxed IP 346 < 3% (64742-62-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.
Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : None under normal conditions.
Symptoms/effects after ingestion : Risk of lung oedema.

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Not to be expected)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Not to be expected).

Heptane, branched, cyclic and linear (426260-76-6)

LC50 - Fish [1]	13.4 mg/l (Oncorhynchus mykiss; OECD TG 203)
EC50 - Crustacea [1]	4.6 – 10 mg/l (Daphnia magna, By analogy to similar materials)
EC50 72h - Algae [1]	29 mg/l (Raphidocelis subcapitata, By analogy to similar materials)
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l (Daphnia magna)
NOEC chronic crustacea	0.17 mg/l (Daphnia magna; OECD TG 211)
NOEC chronic algae	3 mg/l (Raphidocelis subcapitata; OECD TG 201; By analogy to similar materials)

heptane; n-heptane (142-82-5)

LC50 - Fish [1]	3 – 10 mg/l
EC50 - Crustacea [1]	0.4 mg/l
LOEC (chronic)	0.32 mg/l (Daphnia magna)
NOEC (chronic)	1 – 1.6 mg/l

POLYBUTENE (9003-29-6)

LC50 - Fish [1]	> 1000 mg/l (Oncorhynchus mykiss)
NOEC chronic algae	> 100 mg/l

distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LC50 - Fish [1]	> 5000 mg/l
EC50 - Crustacea [1]	> 1000 mg/l

Residual oils (petroleum) solvent dewaxed IP 346 < 3% (64742-62-7)

LC50 - Fish [1]	> 5000 mg/l Source: IUCLID
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID

12.2. Persistence and degradability

VP RACING FOAM FILTER OIL (2917)

Persistence and degradability	Not rapidly degradable
-------------------------------	------------------------

propane (74-98-6)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

butane (106-97-8)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

Heptane, branched, cyclic and linear (426260-76-6)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

heptane; n-heptane (142-82-5)	
Persistence and degradability	Rapidly degradable
POLYBUTENE (9003-29-6)	
Persistence and degradability	Rapidly degradable
distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)	
Persistence and degradability	Rapidly degradable
Residual oils (petroleum) solvent dewaxed IP 346 < 3% (64742-62-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

propane (74-98-6)	
Bioaccumulative potential	Not to be expected.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.
Ecological waste information	: The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols, flammable, n.o.s.	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

DOT	IMDG	IATA
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available		

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN1950
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

IMDG
Limited quantities (IMDG) : SP277
Excepted quantities (IMDG) : E0

IATA
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA max net quantity (IATA) : 75kg

SECTION 15 Regulatory information

15.1. Federal regulations

Nenhuma informação adicional

15.2. International regulations

Nenhuma informação adicional

SECTION 16 Other Information

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations
Issue date : 4/5/2026

Full text of hazard classes and H-statements	
Aerosol 1	Aerosol, Category 1
Aquatic Acute 2	Hazardous to the aquatic environment — Acute Hazard, Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Gas 1A	Flammable gas, Category 1A

VP RACING FOAM FILTER OIL (2917)

Safety Data Sheet

according to Federal Register / Vol. 89, No. 98 / Monday, May 20, 2024 / Rules and Regulations

Full text of hazard classes and H-statements	
Flam. Liq. 2	Flammable liquid, Category 2
Press. Gas (Liq.)	Gas under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurized container; may burst if heated
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), Brazil, Spray Products

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.