4331 EUCALYPTUS AVE. CHINO, CA 91710
Phone 909-597-7800 Fax 909-597-7185

1999-2007 FORD F250/350 SUPER DUTY
FTS136 OR FTS137 6" LIFT COILS

PARTS LIST:

	FTS136	Coil 6" 2wd S/D
Qty	Part #	Description
2	FT136	Coil 98-99 F250/350 S.D. 6IN
2	FT30169BK	Sway Bar Drop Brkt.
1	FT30337	Hdwr. Sub-Assembly Kit
2	FT410-107BK	Bump Stop Drop Brkt.

	FTS137	Coil 6" 2wd S/D
Qty	Part #	Description
2	FT137BK	Coil 98-99 F250/350 S.D. 6IN
2	FT30169BK	Sway Bar Drop Brkt.
1	FT30337	Hdwr. Sub-Assembly Kit
2	FT410-107BK	Bump Stop Drop Brkt.

	FT30337	Hdwr Sub-Assembly Kit
Qty	Part #	Description
12	50000005052	1/2" SAE Flat Washer
12	50130003052	1/2"-13 Nylock Nut
8	50131251052	1/2"-13 X 1 1/4" Hex Cap Bolt
4	50131501052	1/2"-13 X 1 1/2" Hex Cap Bolt
2	FT410-108	Coil Spacer 3/8" X 3"
2	FT136i	Instructions FTS 136
1	FTREGCARD	Registration Card
1	FTAS16	Driver Warning

CHECK ALL PARTS INCLUDED IN THIS KIT TO THE PARTS LIST ABOVE BEFORE BEGINNING INSTALLATION OF THE KIT. IF ANY PIECES ARE MISSING, CONTACT FABTECH AT 909-597-7800

SWAY BAR AND BUMPSTOP DROP BRACKETS, AND COIL SPACERS MUST BE INSTALLED!

Disconnect the negative terminal on the battery. Remove the 4 bolts securing the sway bar mounts to the frame. Place the sway bar drop brackets in between the frame and the mounts. Using the supplied 1/2" x 1 1/4" bolts, nuts and washers, secure the mount to the spacer and the spacer to the frame.

Remove the bolts securing the bump stops to the frame. Using the supplied 1/2" x 1 1/2" bolts, nuts and washers, secure the bump stop drop bracket to the frame. Attach the bump stop to the drop bracket using the original bolt, make sure bump stop is aligned with the locating hole in the drop bracket.

To install the coil spring spacer, remove the nut securing the coil spring onto the I beam. Lift the coil spring off it's mount and slide the mount off of the I beam. Remove the second nut securing the I beam to the radius arm. Place the spacer on the I beam bolt and reinstall the nut. Tighten this nut to 200 ft./lbs. Replace the coil spring mount and the new coil spring. Reinstall the original nut and torque to 60 ft./lbs.

Check front-end alignment and set to factory specifications and re-adjust headlights

RETORQUE ALL NUTS, BOLTS AND LUGS AFTER 50 MILES AND PERIODICALLY THEREAFTER.

For technical assistance call: 909-597-7800

Product Warranty and Warnings-

Fabtech provides a Limited Lifetime Warranty to the original retail purchaser who owns the vehicle, on which the product was originally installed, for defects in workmanship and materials.

The Limited Lifetime Warranty excludes the following Fabtech items; bushings, bump stops, ball joints, tie rod ends, limiting straps, cross shafts, heim joints. These parts are subject to wear and are not considered defective when worn. They are warranted for 60 days from the date of purchase for defects in workmanship.

Take apart shocks are considered a serviceable shock with a one year warranty on leakage only. Service seal kits are available separately for future maintenance. All other shocks are covered under our Limited Lifetime Warranty.

Fabtech does not warrant any product for finish, alterations, modifications and/or installation contrary to Fabtech's instructions. Alterations to the finish of the parts including but not limited to painting, powdercoating, plating and/or welding will void all warranties. Some finish damage may occur to parts during shipping which is considered normal and is not covered under warranty.

Fabtech products are not designed nor intended to be installed on vehicles used in race applications or for racing purposes or for similar activities. (A "RACE" is defined as any contest between two or more vehicles, or any contest of one or more vehicle against the clock, whether or not such contest is for a prize). This warranty does not include coverage for police or taxi vehicles, race vehicles, or vehicles used for government or commercial purposes. Also excluded from this warranty are sales outside of the United States of America.

Installation of most suspension products will raise the center of gravity of the vehicle and will cause the vehicle to handle differently than stock. It may increase the vehicle's susceptibility to a rollover, on road and off road, at all speeds. Extreme care should be taken to operate the vehicle safely at all times to prevent rollover or loss of control resulting in serious injury or death. Fabtech front end Desert Guards may impair the deployment or operation of vehicles equipped with supplemental restraining systems/air bag systems and should not be installed if the vehicle is equipped as so.

Fabtech makes every effort to ensure suspension product compatibility with all vehicles listed in the catalog, but due to unknown auto manufacturers production changes and/or inconstancies by the auto manufacturer, Fabtech cannot be responsible for 100% compatibility, including the fitment of tire and wheel sizes listed. The Tire and Wheel sizes listed in Fabtech's catalog are only a guideline for street driving with noted fender trimming. Fabtech is not responsible for damages to the vehicle's body or tires.

Fabtech's obligation under this warranty is limited to the repair or replacement, at Fabtech option, of the defective product only. All costs of removal, installation or re-installation, freight charges, incidental or consequential damages are expressly excluded from this warranty. Fabtech is not responsible for damages and/or warranty of other vehicle parts related or non related to the installed Fabtech product. This warranty is expressly in lieu of all other warranties expressed or implied. This warranty shall not apply to any product that has been subject to accident, negligence, alteration, abuse or misuse as determined by Fabtech.

Fabtech suspension components must be installed as a complete system including shocks as shown in our current catalog. All warranties will become void if Fabtech parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension parts may cause premature wear and/or product failure resulting in an accident causing injury or death. Fabtech does not warrant products not manufactured by Fabtech.

Installation of Fabtech product may void the vehicles factory warranty; it is the consumer's responsibility to check with their local vehicle's dealer for warranty disposition before the installation of the product.

It is the responsibility of the distributor and/or the retailer to review all warranties and warnings of Fabtech products with the consumer prior to purchase.

Fabtech reserves the right to supercede, discontinue, change the design, finish, part number and, or application of parts when deemed necessary without written notice. Fabtech is not responsible for misprints or typographical errors within the catalog or price sheet.